





A Boundary Line Adjustment Survey for Edna Hammons, Brian Hammons, Bob Tinker, and Tammi Jo Flynn

This document includes: Record of Survey (3 map sheets);

Descriptions - Hammons Parcel (5 pages); Descriptions - Tinker Parcel (5 pages); And Narrative of Survey (this page).

NARRATIVE OF SURVEY

A survey to describe parcels of land per the settlement agreement between the parties to terminate Tinker Brothers Partnership.

This survey commenced in August of 1996 by mapping the residences and access driveway (map sheets 2 and 3). After the parties reached agreement, survey recommenced in March of 1999.

Bearings are GRID, Oregon Coordinate System of 1983, North Zone, and based on observations from Cottonwood 1963 NGS monument and azimuth mark (theta $< 1^{\circ} 35' 27"$).

Tinker / Hammons own property in Sections 13, 24, 25, and 26 of Township 6 North, Range 36 East, WM, and in Sections 18 and 19 of Township 6 North, Range 37 East, WM, Umatilla County, Oregon. This survey monuments only that property within Section 24, Township 6 North, Range 36 East, WM.

Along the Oregon - Washington State Line, I found a pin that I set in 1990 per Book 5 of Surveys, page 132, records of the Walla Walla County Auditor for State Line M.P. 33, and a brass cap at the Northwest closing corner of Section 13 per Map 93-72-B, records of the Umatilla County Surveyor. Repeated searches failed to located either State Line mileposts or Oregon closing corners further to the east. While it was evident that the state line has been preserved as far as can be seen several miles east, the same can not be said for section corners along that line. I use the record distance from the Northwest corner of Section 13 along the latitudinal line to establish the Northeast corner of Section 13.

Narrative of Survey - Page 1 of 2

11-99 KK 99-282-B Searching South along the range line between Ranges 36 and 37 East, I find that no corners or section lines have been preserved for nearly three miles south. I find a fence corner at an East - West with a North fence line for the southeast corner of Section 25.

I establish corners common to Section 24, R36E, and Section 18, R37E, along the Range line by single proportion.

For the Southwest corner of Section 24, I find remains of a fence post and a downed wire fence to the south and east.

As I can find no evidence of the Northwest corner of Section 24, I search 1 mile west and use the centerline of Hood Road with the intersection of the power line from the west as the best location for the Northwest corner of Section 23.

I establish the Northwest corner of Section 24 by double proportion.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

DIGHT M. BARTLESON
021861.5

RUGIS I DEC 31, 1998

Narrative of Survey - Page 2 of 2

Constitution of the second of