

could find no scribe marks on either. I accept this stone as the quarter corner position.

24 19

this survey.

In Survey Number 03-274-C (also filed as M-045-C). Chris Palmer places the Southwest corner

of Section 18 by found bearing trees. A retracement of his survey and a diligent search at his corner

accessories. Placing this section corner by retracement of his survey, I find his position to be suspect

position revealed that he did not monument this corner. I can find no remains of the bearing tree

as it falls significantly West (100± feet) of a proportionate position. Measurements between other

found original monuments of the Currin and Noland survey along the range line reveal no significant

feet of a proportionate position. No chisel marks could be found on any of the excavated stones.

Due to the harmony with the location of this mound of stone with corners to the North, South and

East, I accept this mound as the best available evidence of the original corner monument position. I subdivide the section as per BLM Manual of Instructions 2009. I find no other unusual conditions with

angle discrepancies. I do find a prominent mound of stone, approximately 4 ft. in diameter within 35

BASIS BEARING

True geodetic North at the Southwest corner of Section 19, Township 1 North, Range 35 East of the Willamette Meridian, as determined by GPS observation

SCALE: 1"=600'

## LEGEND

- $\odot$ Found 1" aluminum rod with 2 1/2" aluminum cap, set by BLM Surveyor Bryan Seibold
- Found 1 3/4" iron pipe with 2 1/2" brass cap, **(** set by GLO Surveyor L.E. Wilkes, in dependent resurvey
- Found 2" aluminum cap, marked as per Umatilla County Monumentation Records, set by Survey Number 08-145-B
- Found 2 1/2" aluminum cap, marked as per Umatilla County Monumentation Records, set by Survey Number 13-521-B
- Set 2 1/2" aluminum pipe with 2 1/2" aluminum 0 cap, marked as per Umatilla County Monumentation Records
- Set 5/8" rebar with 2 1/2" aluminum cap, marked as per Umatilla County Monumentation 0 Records, filed separately
- Record measurement as per GLO Special Instructions dated May 4, 1887, executed by Noland and Currin
- Record measurement as per GLO Special Instructions dated Feb. 20 1917, executed by
- Record measurement as per Survey Number 03-274-C (M-045-C)
- Record measurement as per Survey Number 08-145-B
- Record measurement as per Survey Number

Line marked with flagging and paint on adjacent

## REFERENCE MATERIAL

Umatilla County Monumentation Records Survey Number M-045-C

Survey Number M-105-A Survey Number 03-274-C Survey Number S-124-B Survey Number 88-11-B

Survey Number 08-145-B

Survey Number 10-131-B Survey Number 13-521-B

Field Notes of Dependent Resurvey, executed by L.E. Wilkes under GLO special instructions dated Feb. 20, 1917, included in Group No. 29 and approved April 11, 1917

Field Notes of Dependent Resurvey, executed by Bryan S. Seibold, under BLM Special Instructions dated May 19, 1999, included under Group No. 1913 and Assignment Instruction dated May 19, 1999

DEED REFERENCES

Field Notes from GLO Contract dated May 4, 1887, executed by James P. Currin and James E. Noland

Micofilm Document Number 2013-6120651 Microfilm Document Number 2013-6120653

REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON

JUNE 2, 2010 JEFFREY S. HSU 83571

Renewal Date: June 30, 2015

RECEIVED BY

Umatilla County Surveyor Date: 11 03 2014

Rec'd By: G Nensley

No.: 14-137-B

## 🟂 BAGETT, GRIFFITH & BLACKMAN 2006 Adams Avenue, LaGrande, Oregon

Map of Survey Situate in Section 18, Township 1 North, Range 35 East of the Willamette Meridian

UMATILLA COUNTY, OREGON

SURVEYED FOR Hancock Forest Management SURVEYED BY J. S. H. Oct 2014

Scale: 1" = 600'Drawn by: J. S. H.