BOUNDARY SURVEY OF A TRACT OF LAND LOCATED IN THE SW1/4
OF THE SE1/4 OF SECTION 1, T.4N., R.28E., W.M., UMATILLA
COUNTY, OREGON
W.O. 23-6007

I, TODD R. CATTERSON, A REGISTERED PROFESSIONAL LAND SURVEYOR IN THE STATE OF OREGON, ON THE BASIS OF W.O. 23-6007 MY KNOWLEDGE, INFORMATION AND BELIEF, CERTIFY TO MEDARDO VILLARREAL THAT AS A RESULT OF A SURVEY MADE ON THE GROUND TO THE NORMAL STANDARD OF CARE OF PROFESSIONAL LAND SURVEYORS PRACTICING IN OREGON, I HAVE FOUND OR SET THE MONUMENTS AS SHOWN HEREON AND HAVE PREPARED THIS MAP AND NARRATIVE TO REPRESENT SAID SURVEY. SURVEY FOR SURVEY BY FENCE LIES 1(N89*20'W - 95.00') ARMSTRONG SURVEYING, INC. 267 NE SECOND ST. STE. 100 MEDARDO VILLARREAL 1.78' NORTH N89°19'23"W - 95.00' FENCE LIES 1757 E HOOKER RD HERMISTON, OR 97838 SURVEY NARRATIVE PRINEVILLE, OR 97754 (541) 447-7791 WE WERE EMPLOYED BY MEDARDO VILLARREAL TO COMPLETE A BOUNDARY SURVEY OF HIS PROPERTY DESCRIBED IN DEEDS MF 2005-4850113, RECORDS OF UMATILLA COUNTY, OREGON. SEARCH OF THE RECORDS FOUND NO RECORDED SURVEYS IN THE VICINITY OF THIS SURVEY. SUBJECT PROPERTIES DEED MAKES A CALL FOR IRON PINS **LEGEND** SET AT THE CORNERS. SEARCH IN THE FIELD DID NOT RECOVER ANY OF THESE PINS. RESEARCHING THE DEED RECORDS I FOUND NO GAP OR OVERLAP ISSUES WITH THE NEIGHBORING PROPERTIES DEED DESCRIPTIONS. FOR THIS SURVEY HELD DEED RECORD DIMENSIONS ROTATED TO OUR SURVEYED SOUTH LINE OF SECTION 1. THIS SURVEY WAS SET 5/8" x 30" LONG IRON ROD WITH YELLOW PLASTIC CAP MARKED PERFORMED USING A TRIMBLE R10 GPS SYSTEM IN RTK MODE. "ARMSTRONG SURVEYING". FOUND 2" ALUMINUM CAP ON 5/8" IRON ROD AS PER OREGON CORNER RESTORATION FORM BY GARY R. ROBERTS, LS 2627, RECORDED OCTOBER 6, 2005. FENCE LIES 1.30' EAST FOUND 2-1/2" BRASS CAP AS PER OREGON CORNER RESTORATION FORM BY LANCE CLARK KING, LS 61420, RECORDED AUGUST 22, FOUND 1/2" IRON ROD AS PER SURVEY NO. L-096-A BY DENNIS G. EDWARDS, LS 951, RECORDED NOVEMBER 24, 1976. FOUND 1/2" IRON ROD AS PER SURVEY NO. J-038-B BY DENNIS G. EDWARDS, LS 951, RECORDED AUGUST 19, 1975. FENCE LIES 1() RECORD AS PER DEED NO. 2005-4850113 _2.24' EAST 2() RECORD AS PER SURVEY NO. R-134-B BY FAYETTE MUNRO, LS 1632, RECORDED JULY 14, 1980. RECORD AS PER SURVEY NO. 09-173-B BY CURTIS B. STOCKHOFF, LS 2765, RECORDED DECEMBER 2009. RECORD AS PER SURVEY NO. 03-157-A BY WAYNE O. HARRIS, LS REGISTERED 346, RECORDED JULY 7, 1959. PROFESSIONAL 5() RECORD AS PER SURVEY NO. Q-0552-B BY RALPH P. THOMPSON, <u>VILLARREAL</u> MF 2005-4850113 LAND SURVEYOR LS 506, RECORDED MAY 17, 1962. 0.50 AC. \pm add R Catterson RECORD AS PER SURVEY NO. L-096-A BY DENNIS G. EDWARDS. LS 951, RECORDED NOVEMBER 24, 1976. FENCE LIES 3.53' EAST 94/23 OREGON JAN. 15, 2002 TODD R. CATTERSON 7() RECORD AS PER SURVEY NO. J-038-B BY DENNIS G. EDWARDS, LS 951, RECORDED AUGUST 19, 1975. 53270 RM REFERENCE MONUMENT RENEWS 12/31/23 JULY 21, 2023 CNS COMPUTED NOT SET FENCE LIES ----- EXISTING FENCE RECEIVED BY Umatilla County, Surveyor Date: 8 11 23 Rec'd By: CT BASIS OF BEARINGS BEARINGS ARE BASED ON GPS SURVEY MEASUREMENTS USING THE WGS 1984 ELLIPSOID AND A TRANSVERSE MERCATOR MAPPING PROJECTION WITH THE FOLLOWING PARAMETERS: ORIGIN OF LATITUDE = 45'50'57.68800"N ORIGIN OF LONGITUDE = 119*15'32.31418"W SCALE FACTOR = 1.0000000000229.30°) 229.30° $7(N89^{\circ}20'W - 519.42')$ $6(N89^{\circ}20'W - 40.0')$ S89'19'23"E - 95.00' S89°19'23"E - 617.59' S89°18'56"E - 519.41" S89 16'33"E - 40.11' HOOKER ROAD POINT OF BEGINNING MF 2005-4850113 FENCE LIES 2.30' EAST 1(S89'20'E - 95.00') 1(N89°20'W - 562.62') S89°19'23"E - 562.62' 617.59' S89'19'23"E - 95.00' E1/16 \$1 S6 \$12 S7 1329.29' 2(N89'20'W - 1329.31') 3(S89'47'52'W) CNS 1329.30' 2(N89'20'W - 1329.31') 3(S89°47'52"W) 4(1329.75') S89*19'23"E - 2658.59' 5(S89*20'E - 2659.5') 5(N89'14'W)

SURVEYOR'S CERTIFICATE

SHEET 1 OF 1 DRG. NO. 23-6007.DWG

23-6007