CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The corner was monumented in 1998, by Kaiser/Griffin/ Seibold, Cadastral Surveyors under Bureau of Land Management Group No. 1844. The field notes state:

Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap from which:

A ponderosa pine, 17 ins. diam., bears S.84°W., 73 lks. dist., mkd. C 1/4 S6 BT A ponderosa pine 19 ins. diam., bears N.87-1/2°W., 69 lks. dist., mkd. X at breast height and BT at the base.

Deposited a magnet in a white plastic case at the base of the stainless steel post.

Description of corner evidence found:

Found 3-1/4" BLM brass cap marked per the diagram, 0.4 feet above the ground from which: 18" Ponderosa Pine bears S.84°W., 48.2 feet, (BLM bearing tree). 19-1/2" Ponderosa Pine bears N.87°30'W., 45.5 feet, (BLM bearing tree).

Description of monument and accessories I established to perpetuate the original location of this corner:

16" Douglas Fir bears N.67°E., 22.5 feet, scribed "C1/4S6BT" 14" Douglas Fir bears S.81°E., 20.3 feet, scribed "XBT".

All new bearing trees are single blazed and scribed with brass washer "PLS2535" attached to the BT portion. Appropriate signs have been attached to all bearing trees as required by this US Forest Service contract. 20° declination was used. Fieldwork was performed in July and August 2002.

REGISTERED PROFESSIONAL LAND SURVEYOR

DIAGRAM

C 1/4

T1N R36E

1998

C-03

S6

OREGON 11/0 JAN. 21, 1992 MICHAEL P. LE JEUNE

EXPIRES 12/31/02

Prepared by:

White Shield, Inc. P.O. Box 477 Grandview, WA 98930 Michael P. LeJeune, Oregon PLS. 2535

Office ofegunty Surveyor, County ofWallows	State of Oregon, I hereby certify that the with the Y
instrument was filed in this other or record on the	day of
(County Official)	(Deputy) Date 1/-02
	No. 02-273-B