CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: This corner was originally established by Rufus S. Moore on October 2, 1882, under Contract No. 451 as follows:

Intersect East boundary of township 580 links south of the corner to Sections 6 & 7, T.1S., R.36E.

Set a basalt stone 24" \times 10" \times 3", 18" into the ground for the closing corner marked "CC" on the west, 5 notches on the south and one notch on the west edges, from which:


DIAGRAM	
TIS	
C. <u>S1</u> S7	TIS
c. \$12	R36E
R35E	

a 30" pine bears ${
m N42^oW}$, 162 links marked "CC TIS R35E SI BT". Raise a mound of stone alongside corner.

Description of corner evidence found: Original corner stone, 3" x 10" x 24", is lying loose on top of a mound of stones. Stone mound is 4 feet in diameter and 1 foot high. Corner stone is plainly marked:

The original B.T. has fallen and is nearly decayed away. No marks remain. A slight depression where the tree once stood bears N420W, 106.9 ft.

The brass capped, monumented corner to Sections 6 & 7, T.1S., R.36E., bears north, 386 feet (record is north, 382.8 ft.).



Description of monument and accessories I established to perpetuate the original location of this corner:

on a single blaze bears S60°W, 66.2 feet.

Moving the corner stone aside, I find a depression in the center of the stone mound where the corner stone was originally set. In the center of this depression, I set a 5/8" x 24" Iron Rod with a $1\frac{1}{2}$ inch Aluminum cap attached, 21 inches into the ground. The cap is marked:

From which new bearing trees:

A 16" ponderosa pine, scribed "T1S R35E S1 CC BT"

on a single blaze, bears N51°W, 114.2 feet.

A 12" ponderosa pine, scribed "T1S R35E S12 CC BT"

A 12" ponderosa pine, scribed "T1S R35E S12 CC BT"

PLS 1636

Both bearing trees have a 3/4" brass washer, marked "PLS 1636", nailed flush on the lower portion of the blaze, and have signs 54-3 "Bearing Tree" and 54-4, "Warning", signs attached.

I hereby certify the above original closing corner position was perpetuated as hereon described on July 11, 1985.

REGISTERED De: 20°E

PROFESSIONAL LAND SURVEYOR

OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1638

Office of... County Surveyor County of Umatilla

State of... Oregon I hereby certify that the within instrument was filed in this office for record on the day of 19...

(COUNTY OFFICIAL)

OREGON
JULY 14, 1978

OUT 11. 1978

OUT

Form R6-7100-57 (9/71)

No. 85-85-K

No. 85-85-K

No. 85-85-K

No. 85-85-K