| Index File NoA-18 T1S R36E MeridWILLAMETTE | CORNER RECORD (SEARCH) Tract or Cor. (Ref. FSM 7151.4) Survey No. No. No R.D. <u>WALLA WALLA</u> County <u>UMATILLA</u> N.F. <u>UMATILLA</u> State <u>OREGON</u> |
|---|---|
| CORNER DIAGRAM | DESCRIBE CORNER MONUMENT FOUND |
| | Corner not previously established. |
| S 2 | DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND Corner not previously established. |
| | <u>.</u> |
| PHOTO IDENTIFICATION DATA | · |
| Photo No Filed At | |
| Object Ident | DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER |
| Signature 7 | Corner falls on steep West face approximately |
| PLANE COORDINATE POSITION DATA State Zone X Y | South of the point of the ridge running Northwest. BLM Corner monument for the standard South ¼ corner of Section 35, T1N R36E is East 3.42 feet from 1/16 corner monument. |
| Estab. By Aggsy 8 | 4 |
| hum dignatur | Title Division Headquarters Date FS-7100-52 (3/68) Surveyor 9-19-89 5 |

A

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT **T1N R36E** Set a 2½"x30" aluminum pipe with aluminum cap marked as shown: Pipe is set 28 inches in the ground. W1/16 S 2Raised a mound of stone around monument, 3 ft. base to top of cap. T1S R36E 1989 **OPLS 644** ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE New Bearing Objects: A 5/8"x30" iron pin with plastic cap marked BGA SURVEY MARKER bears S30°E, 11.36 feet A 1/2"x24" iron pin with plastic cap marked BGA MARKER bears S23°W, 11.11 feet Attached Bearing Tree sign to the bearing objects. Set a steel fence post approximately 1 foot East with 54-9 sign attached. 9-14-89 State Registration No. OPLS 644 Surveyor

Work Done By. I. Griffith Title Filed Al: Umatilla Co. Surveyor's Office Date 9-89 Certified Cor. Record Prepared ? Yes REMARKS

Jeff Petersen and Rick Robinson Witnesses:

Index File No. R. 36E W.M. Tract or Surv. No.

Cor.

13