H-162

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1882 by Herman D. Gradon, under General Land Office Contract #452. Surveyor General Records (notes) states:
Set a post 4 ft. long, 4 ins. square, 24 ins. in the ground for the corner to Secs. 21, 22, 27, and 28, marked
T1S S22 on NE
R36E S27 on SE
S28 on SW and
S21 on NW faces, with 2 notches on south and 3 notches on East edges, from which
A tamarack 11 ins. dia. bears N 55° E 17 lks. dist marked T1S R36E S22 BT
A tamarack 8 ins. dia. bears S 12° E 40 lks. dist. marked T1S, R36E S27 BT
A Tamarack 9 ins. dia. bears S 28° W 26 lks. dist. marked T1S, R36E S28 BT
A Pine 7ins. dia. bears N 15° W 12 lks. dist. marked T1S, R36E S21 BT

(No subsequent remonumentations in county records.

DIAGRAM	
T 1 S	R 36 E
S 21	S 22
S 28	S 27

R-13

Description of corner evidence found:
Found original post rotted off 18" above the ground marked T1S, S22 on NE face R36E Sec. 27 on SE face S28 on SW face. NW face is rotted away.
Found a down and dead tamarack 12 ins. dia. with scribing visible, bearing N 55° E 11 ft. dist. from the post.
Found a down and dead tamarack 10" dia. with scribing visible, bearing S 28° W 17.2 ft. distance from the post.

Description of monument and accessories I established to perpetuate the original location of this corner
At the location of the found post, set a 2½"x30" iron pipe with 3" brass cap marked as shown for the corner to section 21, 22, 28, & 27, from which new BT's
A fir 16" dia. bears N 37° E 18.3 ft. dist marked T1S R36E S22 BT
A fir 25" dia. bears S 75° E 14.4 ft. dist. marked T1S R36E S27 BT
A fir 12" dia. bears S 54° W 19.3 ft. dist. marked T1S R36E S28 BT
A fir 7" dia. bears N 25° W 17.7 ft. dist. marked "X" BT
All distances taken to a brass washer in the blaze of each tree.
Set a steel fence post approximately 5' NE from corner with Attention sign attached



Used steel tape and magnetic compass with declanation --20° East

Office of [illegible] County of [illegible]
State of [illegible], I hereby certify that the within instrument was filed in this office for record on the [illegible] day of [illegible], 19[illegible], at ..... o'clock .....m., (signed) [illegible] by .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)

H-162