


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

G - 17  
DIAGRAM

History of original corner establishment:

The original corner was established by David P. Thompson on August 30, 1859, under GLO contract No. 83, as follows:

Set a post for 1/4 section corner with a mound of earth & etc., per instructions.



On November 18, 1904, County Surveyor John W. Kimbrell set a stone for the 1/4 section corner with mound, pits & etc.

On June 15, 1999, Gary B. Wagner, PLS 2817, found a granite stone 6" x 4" x 18" with "X" on top. See County Survey Map No. 99 - 133 - B.

Original corner evidence recovered:

Found a white, quarried, granite stone solidly set 23" into the ground. The corner stone is 29" x 6" x 5" and is plainly marked "1/4" on top.

Monument and accessories established to perpetuate the original position of this corner:

In place of the recovered stone, I set a 1" x 30" flared, galvanized iron pipe 27" into the ground. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above. I bury the corner stone along the southeast side of the pipe, from which:

A 5/8" x 24" iron rod set 23" into the ground, with a 3/4" brass washer, marked "PLS 1636 NE", attached at ground level, bears N44° E, 82.8 feet.

A 5/8" x 24" iron rod set 23" into the ground, with a 3/4" brass washer, marked "PLS 1636 SE", attached at ground level, bears S37° E, 112.7 feet.

A 5/8" x 24" iron rod set 23" into the ground, with a 3/4" brass washer, marked "PLS 1636 SW", attached at ground level, bears S34° W, 117.7 feet.

A 5/8" x 24" iron rod set 23" into the ground, with a 3/4" brass washer, marked "PLS 1636 NW", attached at ground level, bears N33° 30' W, 102.4 feet.

I nail a "Witness Post" sign to a wood fence corner post which bears N70° W, 1.0 foot from the corner. Wire fences project north and west from this corner post, and the remains of a down fence project east.

I hereby certify the above corner point was perpetuated as hereon described on November 4, 2003. Magnetic declination set in compass: 12° E. (Local attraction from wires on fence).

NAD '83 UTM Zone 11 position: 5059238N, 341293E (plus or minus two meters).

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*Dennis L. Gaylord*  
OREGON  
JULY 14, 1978  
DENNIS L. GAYLORD  
1636

RECEIVED BY  
Umatilla County Surveyor  
Date 2-04  
Rec'd By KK  
No. 04-31-R

Renews June 30, 2005

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on: