

OREGON CORNER RESTORATION FORM

COUNTY: Umatilla DATE: 4/14/94

CORNER DESIGNATION: V-9. Northeast corner Section 32, T2N., R32E., W.M..

PREVIOUS RENEWALS/SURVEYS, ETC.: The original survey was made by Daniel Chaplin, under Contract No. 107, dated September 21, 1864. Set stone 16 x 10 x 10 inches. James P. Currin and James Noland, under Special Contract dated May 4, 1887, found 16 x 10 x 10 inch stone firmly set in ground.

MONUMENT AND ACCESSORIES FOUND: None. Corner falls in farm field.

MONUMENT MARKING DETAIL:

T2N R32E
S29 — S28
S32 — S33
1994
PLS 1106

MONUMENT SET: Re-established corner position by double proportion measurement between the North 1/4 corner of Section 32, the Northeast corner of Section 33, the East 1/4 corner of Section 29, and the Southeast corner of Section 32 and set a 2 1/2" brass cap on a 1 1/4" x 30" galvanized iron pipe, buried 43" in the ground, (marked as shown in the monument detail).

New Accessories:

Gate post with witness sign attached bears West-14.5 feet.
A 5/8" x 30" iron pin with yellow plastic cap stamped "OR PLS 1106-WA PLS 17372" bears N 41° E-17.2 feet, top set 1.1 feet below ground.
A 5/8" x 30" iron pin with yellow plastic cap stamped "OR PLS 1106-WA PLS 17372" bears S 58° E-21.2 feet, top set 0.8 feet below ground.
A 5/8" x 30" iron pin with yellow plastic cap stamped "OR PLS 1106-WA PLS 17372" bears S 8° W-22.3 feet.
A 5/8" x 30" iron pin with yellow plastic cap stamped "OR PLS 1106-WA PLS 17372" bears N 57° W-33.2 feet.
Attached bearing object signs to iron pins. Set steel fence posts near the iron pins, that are above ground, with witness signs attached.

LOCATION & COMMENTS: Corner falls in farm field 15 feet East of East fence on Birch Creek Road.

COMPASS DECLINATION: 18° East.
FIRM/AGENCY: William R. Wells, PLS
P.O. Box 1696
Pendleton, Oregon 97801

Surveyor's Seal

Party Chief: Robert D. English
Notes: Robert D. English
Witness: F. Scot Munro

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1994
WILLIAM R. WELLS
1106

renew 12-31-94