USDA-FO	DREST	SERVIC	E					
Index File No. <u>WB 1028</u>				CORNER RECOI	ND (SEARCH) M 7151.4)	Tract or Survey No	•	Cor. No.
T 2N		. r. <u>37</u> E		R.D. WALLA WALLA	County _	UMATILLA		
Merid	WIL	LAMET1	<u>'E</u>	N.F. <u>UMATILLA</u>	State	OREGON		
CORNER DIAGRAM				DESCRIBE CORNER MONU	MENT FOUND			
				Corner not previ	ously estal	blished.		
	WB	1028	[·			
	s	(11 !	 	DESCRIBE BEARING TREES			S FOUND	2
, .		•	J 6	No accessories p	reviously 6	established.		
PHOTO ID	ENTIFIC	ATION D	ATA	1				
Photo No.								
Filed At.								3
Object IdentIdent. By				DESCRIBE CORNER LOCATI	ON RELATIVE TO	NEAR-BY FEATUR	ES, ALSO HOW	TO REACH CORNER
PLANE COORDINATE POSITION DATA				Corner falls in South of the end	draw approx of the 315	kimately 900 : 50-211 road.	feet	
State		Zone						
×								
Estab. By	 .							
		Agency	8	<u>.</u>				4
Alema	Sig	natur	11/	Title Divisi	on Head	quarters	Date	FS-7100-52 (3/68)
	- 64	/		SURVEYOR			9-6-91	5

CORNER RECORD (PERPETUATION)

Filed Ar. Umatilla Co. Surveyor Off.

Date 7-15-91 State Registration No.

MONUMENT :: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set a 2½"x30" aluminum pipe with aluminum cap marked as shown: Pipe is set 24 inches in the ground.

ELEV 4600

WB **/028** 1991 OPLS 644

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

New BTs:

A 19 inch diam. Ponderosa Pine bears S20°W, 57.73 feet marked WB 1028 BT A 24 inch diam. Douglas Fir bears N64°W, 47.77 feet marked WB 1028 BT

Attached Bearing Tree and Land Survey Monument signs to the BTs Set a steel fencepost approximately 5 feet Westerly with Land Survey Monument and Wilderness Boundary signs attached.

OPLS 644 10-91

10

12

REMARKS

Witness: Jim Bennett

Tract or Surv. No. Cor. 13

Date

GPO: 1984 O - 439-095

Index File No.WB 1028 T.ZN R.

Certified Cor. Record Prepared ? Yes 👼 No.

Work Done By. D. I. Griffith ____ Title _ Surveyor

R. 376

WM.