## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

T2S R30E

1/4 S22

The original corner was established by George S. Pershin on
September 5, 1878, under GLO contract No. 293, as follows:

PLS 1636

2002

Set a stone, 20" x 12" x 10", on west side of ridge for the 1/4
section corner.

## Original corner evidence recovered:

Found the original corner stone loosely set in a mound of stones. The corner stone is 21" x 11" x 8" and is plainly marked "1/4" on one face.

## Monument and accessories established to perpetuate the original position of this corner:

In place of the original corner stone, I set a 1" x 30" flared, galvanized iron pipe 19" into the ground to bedrock. A 2 1/2" brass cap attached to the top of the iron pipe is marked as shown in the diagram above. I bury the corner stone along the east side of the pipe and build a mound of stones around the pipe, from which:

A 5/8" x 24" iron rod, set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 NE", attached at ground level, bears N27° 30' E, 76.8 feet.

A 5/8" x 18" iron rod, set 15" into the ground with a 3/4" brass washer, marked "PLS 1636 SE", attached at ground level, bears S54° 30' E, 140.9 feet,

A 5/8" x 24" iron rod, set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 SW", attached at ground level, bears S28° W, 80.7 feet.

A 5/8" x 24" iron rod, set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 NW", attached at ground level, bears N33° W, 80.2 feet.

I nail a "Witness Post" sign to a wood post one foot southwest of the corner.

I hereby certify the above corner point was perpetuated as hereon described on June 5, 2002. Magnetic declination set in compass: 18° E.

PROFESSIONAL AND SURVEYOR

OREGON JULY 14. 1978 DENNIS L. GAYLORD

Renews June 30, 2003

Recorded at the office of County surveyor, County of Umatilla, State of Oregon, on: