CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V - 9 DIAGRAM T2S R30E S29|S28 S32|S33 PLS 1636 2002

History of original corner establishment:

The original corner was established by George S. Pershin on September 7, 1878, under GLO contract No. 293, as follows:

Set a stone, 18" x 10" x 7", for corner to sections 28, 29, 32 and 33. Dug pits and drove a willow stake as per instructions.

Original corner evidence recovered:

Found the original corner stone loosely set on the south edge of a mound of stones. The corner stone is 18" x 10" x 7" and is plainly marked with three notches on one (east) edge and five notches on another (north) edge. The stake and pits of record are gone.

Monument and accessories established to perpetuate the original position of this corner:

In place of the original corner stone, I set a 1" x 18" flared, galvanized iron pipe 12" into the ground to bedrock. A 2 1/2" brass cap attached to the top of the iron pipe is marked as shown in the diagram above. I bury the corner stone along the south side of the pipe and build a mound of stones around the pipe, from which:

A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 28", attached at ground level, bears N41° E, 109.0 feet.

A 5/8" x 18" iron rod set 17" into the ground with a 3/4" brass washer, marked "PLS 1636 33", attached at ground level, bears S54° 30' E, 93.5 feet.

A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 32", attached at ground level, bears S43° 30' W, 108.9 feet.

A 5/8" x 18" iron rod set 17" into the ground with a 3/4" brass washer, marked "PLS 1636 29", attached at ground level, bears N48° W, 124.2 feet.

I hereby certify the above corner point was perpetuated as hereon described on February 13, 2002. Magnetic declination set in compass: 16° E.

PROFESSIONAL LAND SURVEYOR

OREGÓN JULY 14, 1978 DENNIS L. GAYLORD

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on:

RECEIVED BY

Umatilla County Surveyor

Date 6-02

Rec'd By

Na 02-155-R