CERTIFIED RECORD OF LAND CORNER MONUMENTATION

X - 5 DIAGRAM

History of original corner establishment:

The original corner was established by John C. Arnold on October 4, 1891, under GLO contract No. 551, as follows:

Set a basalt stone, 14" x 8" x 6", 10" into the ground, marked 1/4 on the west face, in a mound of stones on a east hillside.

T2S R32E 1/4 S31|S32 PLS 1636 1998

Corner evidence recovered:

Found the original corner stone loosely set in a mound of stones in a fence corner. Barbed-wire fences project north, east and west. The corner stone is 12" x 10" x 7" and is plainly marked "1/4".

Monument and accessories established to perpetuate the original location of this corner:

On the southwest edge of the mound of stones, I set a 1" x 30" iron pipe 13" into the ground to bedrock. I bury the corner stone along the southeast side of the pipe and build a mound of stones around the pipe to the cap. A 2 1/2" brass cap attached to the pipe is marked as shown in the diagram above, from which:

A 5/8" x 24" iron rod set 20" into the ground with a 3/4" brass washer, marked "PLS 1636 NE", attached at ground level bears N51°E, 46.0 feet. A 5/8" x 24" iron rod set 22" into the ground with a 3/4" brass washer, marked "PLS 1636 SE", attached at ground level bears S17°30'E, 63.5 feet. A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 SW", attached at ground level bears S63°30'W, 75.2 feet. A 5/8" x 24" iron rod set 23" into the ground with a 3/4" brass washer, marked "PLS 1636 NW", attached at ground level bears N59°W, 120.0 feet.

I hereby certify the above corner point was perpetuated as hereon described on September 15, 1998. Magnetic declination: 18 E.

PROFESSIONAL LAND SURVEYOR

DENNIS L. GAYLORD

Renews June 30, 1999

RECEIVED BY

Umatilla County Surveyor

Date 12-98

Rec'd By KK

marie and