


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. W-(1-3)

History of original corner establishment:

No corner was originally set.




Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

At surveyed point set 2 1/2"x30" galvanized pipe with brass cap stamped:

Set pipe 18" in ground with mound of stone to cap.



Bearing Trees:


A Ponderosa Pine 24" dia. bears S81°E 212.2 ft, scribed N 1/16 S31 BT.

A Ponderosa Pine 16" dia. bears S66°E 233.6 ft, scribed N 1/16 S31 BT.

Attached 54-3 & 54-4 signs to both BT's. Attached brass washer stamped LS1294 to foot blaze of both BT's. Painted blazes and 6" band around both BT's Red. Attached 54-2 & 54-4 signs to metal post 5' east of corner. Attached 54-2 & 54-9 signs to metal post 5' south of corner.

I hereby certify the above corner monument was established as herein described on August 22, 1980.

Witnesses: R. Orton  
G. Wagoner  
G. Lester  
J. Anderson



Office of... County Surveyor..... County of..... Umatilla  
 Oregon..... I hereby certify that the within instrument was filed in this office  
 for record on the..... day of... December..... 19.80  
 Howard L. Perry..... by Betty Shatto  
 (COUNTY OFFICIAL)..... (DEPUTY)