ndex File No. <u>MP 67 1/2</u>	CORNER RECORD (SEARCH) Tract or Cor. (Ref. FSM 7151.4) Survey No
r <u>2S</u> R . <u>34E</u>	
Merid. <u>Willamette</u>	_ N.F. <u>Wallowa-Whitman</u> State <u>Oregon</u> ,
ORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
UIR . MP 67 1/2	Found 15 X 12 X 6 inch stone firmly set and marked UR on north side.
	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
PHOTO IDENTIFICATION DATA Photo No.	From which by magnetic declination of N20°E: A 30" pine bears N46°E, 115.7 ft, with partially opened blazes and scribing. A 24" fir bears N82°W, 217.8 ft. with visible scribing on partially open blaze.
Filed At.	
Object identident. By	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
PLANE COORDINATE POSITION DATA	
StateZone X	
Estab. By	
a war as I Sign Heling.	P. Title S. Division / Headquarters Date 7100-52-(3/68)

CORNER RECORD (PERPETUATION)

NUMENT DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT	
At the center of the above stone, set 2 1/2" X 30" galvanized pipe and brass cap marked:	T2S R34E UIR
Set pipe 22" in the ground and mound of stone around to cap.	67 1/2 MP
Buried marked stone alongside.	OR PLS 1051
	1980
CESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESER	EVE EXISTING EVIDENCE
From which by magnetic declination of N20°E:	
A 12" pine bears S42°E, 18.2 ft. scribed UIR MP 67 1/2 BT.	Painted blazes
red and 6" red band around. Placed 54-3, 54-4, and brass wash	ner stamped PLS
1051 on the BT. Placed 54-2 and 54-4 on a steel fence post 5	east of the

Work Done By. <u>B. B. Barbour</u>	Title P. L. S.	Date <u>11-6-80</u> State Registr	otion No. OR 1051	
Certified Cor. Record Prepared ? Yes	No Filed Al. Union	County Surveyor's	Date	1
	REMARKS			
Witnesses:	Daniel Rowland			
	Doug Moser			

Ron Gilroy

Cor.

Τ.

Index File No.

R.

M.

Tract or Surv. No.

Index File No. <u>MP 67 1/2</u>	CORNER RECORD (SEARCH) Tract or Cor. — (Ref. FSM 7151.4) Survey No No
r <u>2S</u> R. <u>34E</u>	
Merid. <u>Willamette</u>	N.F. <u>Wallowa-Whitman</u> State <u>Oregon</u>
ORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
UIR MP 67 1/2	Found 15 X 12 X 6 inch stone firmly set and marked UR on north side.
	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
PHOTO IDENTIFICATION DATA Photo No.	From which by magnetic declination of N20°E: A 30" pine bears N46°E, 115.7 ft. with partially opened blazes and scribing. A 24" fir bears N82°W, 217.8 ft. with visible scribing on partially open blaze.
Filed At.	
Object Ident	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
PLANE COORDINATE POSITION DATA	
State Zone X	

CORNER RECORD (PERPETUATION)		
MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT		
At the center of the above stone, set 2 1/2" X 30" galvanized pipe and brass cap marked:	T2S R34E UIR	
Set pipe 22" in the ground and mound of stone around to cap. Buried marked stone alongside.	67 1/2 MP OR PLS 1051 1980	9
ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERV	E EXISTING EVIDENCE	
red and 6" red band around. Placed 54-3, 54-44, and brass washe 1051 on the BT. Placed 54-2 and 54-44 on a steel fence post 5' corner.	er stamped PLS east of the	lo
Work Done By B. B. Barbour Title P. L. S. Date 11-6-80 State Registration of Agency	on No. OR 1051	
Certified Cor. Record Prepared ? Yes X No Filed At. Union County Surveyor's	Date	11
REMARKS		
Witnesses: Daniel Rowland Doug Moser Ron Gilroy		

Tract or Surv. No.

Index File No.

Τ.

R.

M.

Cor.