USDA-FOREST SERVICE	e e e e e e e e e e e e e e e e e e e
Index File No. <u>WB 921</u>	CORNER RECORD (SEARCH) Tract or Cor. (Ref. FSM 7151.4) Survey No No
T <u>3N</u> R. <u>37E</u>	R.D. WALLA WALLA County <u>UMATILLA</u>
Merid. <u>WILLAMETTE</u>	N.F. <u>UMATILLA</u> State <u>OREGON</u>
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
S 36	Corner not previously established.
WB 921	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND No accessories previously established.
PHOTO IDENTIFICATION DATA	<u>6</u>
Photo No	_
iled At.	,
Object Identdent. By	- TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
LANE COORDINATE POSITION DATA State Zone	200 feet worth of top of ridge and 300 feet North
<	-] .
Estab. By	
Signature Signature	Title Division Headquarters Date FS-7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE ENTINGMONUMENT Set a 2½"x30" aluminum pipe with aluminum cap marked as shown: Pipe is set 28 inches in the ground.

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE New BT and BO:

A 5 inch diam. Douglas Fir bears N80°E, 26.5 feet marked X BT A 5/8"x30" iron pin bears N85°W, 18.25 feet.

Attached Bearing Tree and Land Survey Monument signs to the BT Set a steel fencepost approximately 5 feet South with Land Survey Monument and Wilderness Boundary signs attached.

Work Done By D.I. Griffith Titl	Surveyor	10-10-92state Registration No.	OPLS 644	10
Certified Cor. Record Prepared ? Yes	Filed At: Um	atilla Co. Surveyor Off. Date	10-92	<u></u>

REMARKS

Witness: Jim Bennett

Index File No. T. Tract or Surv. No. GPO: 1984 O - 439-095

Cor.

13