CERTIFIED RECORD OF LAND CORNER MONUMENTATION

G - 17 DIAGRAM

T3S R31E

History of original corner establishment:

The original corner was established by George S. Pershin on May 5, 1879, under GLO contract No. 319, as follows:

1/4 S10|S11 PLS 1636 1998

Set a basalt stone, 18" x 12" x 5", on the north side of a ravine opening westward, from which:

A Pine, 42" in diameter, bears S28°E, 104 links (68.64 feet).

Corner evidence recovered:

The corner stone is loosely set in a mound of stones. The stone is $20" \times 12" \times 5"$ with some chisel marks visible, most have spalled off. The 42" Ponderosa Pine is down and decayed. No marks remain. The root hole bears 812°E, 68.6 feet.

Monument and accessories established to perpetuate the original location of this corner:

At the point occupied by the original corner stone, I set a 1" x 30" iron pipe, 27" into the ground. I bury the corner stone along the south side of the pipe and build a mound of stones around the pipe to the cap. A 2 1/2" brass cap attached to the pipe is marked as shown in the diagram above, from which:

A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer attached at ground level, marked "PLS 1636 NE", bears N34°E, 67.1 feet.

A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer attached at ground level, marked "PLS 1636 SE", bears S11°E, 48.1 feet.

A 9" Hawthorn scribed "1/4 S10 BT" on double blazes, with a 3/4" brass washer nailed flush to the scribed "B", bears S11°W, 14.4 feet. A "Bearing Tree" sign is nailed above the blazes.

A 5/8" x 36" iron rod set 35" into the ground with a 3/4" brass washer attached at ground level, marked "PLS 1636 NW", bears N46 30'W, 80.5 feet.

I hereby certify the above corner point was perpetuated as hereon described on March 25, 1998. Magneitc declination: 18°E.

PROFESSIONAL LAND SURVEYOR

OREGON /

mis V.9

1636 240WY 6/30/1999

Recorded at the office of County Surveyor, County of Umatilla, State of Oregon, on ______, 1998.

RECEIVED BY

Umatilla County Surveyor

Date.

98-4