| USDA-FOREST SERVICE            |  | •                          | * * *            | •                          |
|--------------------------------|--|----------------------------|------------------|----------------------------|
| Index<br>File No. X-16         | CORNER RECORD (Ref. FSM                                    | (SEARCH) Tract or Survey N | o. Sec 34        | Cor.<br>No. <u>CE 1/16</u> |
| T3SR31E                        | _R.D <u>Ukiah</u>  | _ County <u>Umatilla</u>   | 0. <u> </u>      | _ NO <u>QL_1/10</u>        |
| Merid. <u>Willamette</u>       | N.FUmatilla  | _ StateOregon              |                  |                            |
| CORNER DIAGRAM                 | DESCRIBE CORNER MONUME                                     |                            |                  |                            |
| T3S R31E                       | None.  |                            |                  |                            |
| <b>∠</b> E 1/16                | 1 TOILE !  |                            | •                |                            |
| 1 0                            |  |                            | · ·              |                            |
| \$34                           |  | •                          |                  |                            |
| N 334                          | 1  | •                          |                  |                            |
|                                | DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND |                            |                  |                            |
| İ                              | None.  | WOULD OF HOLE HOUESSON     | ILS FOUND        |                            |
| 1                              |  | -                          |                  |                            |
|                                |  |                            |                  |                            |
| 6                              |  |                            | -,               |                            |
| PHOTO IDENTIFICATION DATA      |  |                            | *                | •                          |
| Photo No.                      |  |                            | , · · ·          |                            |
| Filed At.                      |  | - :                        |                  |                            |
| Object Ident.                  | DESCRIBE CORNER LOCATION                                   | RELATIVE TO NEAR-BY FEAT   | URES, ALSO HOW T | O REACH CORNER             |
| Signature -                    | Road #5420 to road   | #5412-100, then West       | on road #5/12.   | -100                       |
| PLANE COORDINATE POSITION DATA | 1.4 miles to road fo                                       | rk Southwest through go    |                  | - 100 approx.              |
|                                | West on road approx  | imate by 0.2 mile if       | ire, mrough go   | ate and South-             |
| State Zone                     | west on road approx  | imately 0.3 mile then 1    | North /00 ff to  | corner in                  |
| \$                             | clearing in timber a                                       | t West edge of Swiss Fl    | at.              |                            |
| Estab. By                      |  |                            |                  |                            |
| Agency 8                       |  | •                          |                  | •                          |
| Signature                      | Title Division   | Headquarters               | Date             |                            |
| Willen K. Wells                | PLS 1106   |                            | rober 25, 1982   | 7100-52 (3, 68)            |
|                                |  | . 00                       | ODEI 23, 1902    |                            |

## CORNER RECORD (PERPETUATION)

NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT Set 2 1/2" brass cap on 2 1/2" x 30" I, pipe 18" in ground with mound of stone. Set steel fence post with \$4-2 and 9 signs attached North of corner. Cap marked:

1982 ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESER

A 7" dia Fir bears S77°W 81.2 ft dist marked: CE 1/16 S34 BT. A 7" dia Fir bears N26°W 75.7 ft dist marked: CE 1/16 \$34 BT.

Blaze faces and 6" bands around bearing trees are painted red. Tagged trees with 54-3 and 9

signs. BTs have a lower blaze, scribed BT, with a brass washer stamped PLS 1106 nailed flush.

W.R. Wells Work Done By.\_\_\_ Surveyor Title Filed Al: Umatilla County Surveyor Office Certified Cor. Record Prepared ? Yes X No Date REMARKS

Witnessed by: R.D. English PC D. L. Kaufman PLS

Tract or Surv. No. Cor. W.M. Sec 34

T. Index File No.

R. M. 35 31<u>E</u>

CE 1/16

T3S R31E

E 1/16

**S34**