


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. V-17

**History of original corner establishment:**

In 1882, under GLO Contract No. 451, Rufus S. Moore set stone 18x15x6. A 4" Pine bears N40°W, 44 lks. An 18" Pine bears N40°E, 133 lks. A 7" Pine bears S73°W, 57 lks.



**Description of corner evidence found:**

Found stone of the proper dimensions, but with no marks, with a mound of stones along the east side.

**Bearing trees found:**

A triple pine stump bears N40°E, 87.8 ft., scribing visible "S26 BT".

**Description of monument and accessories established to perpetuate the original location of this corner:**

Set 3 1/2" aluminum cap on 2 1/2" x 30" aluminum pipe rising 14" in mound, stamped:

T3S	R33E
S27	S26
S34	S35
LS 1848	
1983	

**New BT's:**

- A 6 1/2" D. Fir bears N69 3/4°E, 31.5 ft., scribed T3S R33E S26 BT.
- A 6" D. Fir bears S71°W, 23.6 ft., scribed T3S R33E S34 BT.
- An 8" D. Fir bears N65 1/2°W, 18.4 ft., scribed T3S R33E S27 BT.
- A 14 1/2" D. Fir bears S71 1/2°E, 4.7 ft., scribed T3S R33E S35 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set metal fence post 5 ft. north of corner.

Compass Declination: 19 1/2°E

Witness: D. Scott

From USFS Rd. 2110-220, take 2110-250 .75 mi. to end of rd. Cross clear-cut through fringe of trees to E-W clearing. Follow clearing west to where it turns south. Corner is downhill 100 ft. just on fringe of trees.

I hereby certify the above described corner monument and/or accessories was established as described on November 18, 1983.



Office of Surveyor County of Wasatch  
 State of Oregon I hereby certify that the within instrument was filed in this office  
 for record on the 10th day of July, 1984.  
David Kumbien by Betty Cochran  
 (COUNTY OFFICIAL) (DEPUTY)