OREGON CORNER RESTORATION FORM

COUNTY: Umatilla

DATE: October 19, 2011

CORNER DESIGNATION: J-21 Southeast Corner Section 11, T. 4 North, Range 29 E.W.M.

PREVIOUS RENEWALS/SURVEYS ETC.

Timothy Davenport set a post in mound with charred stake (Contract No.101, dated 1861)

John Kimbrell found corner in a 1905 survey for Inland Irrigation Company, Survey #233, Book 2, Page 16, December, 1905.

G. Dennis Edwards, PLS 951, calculated corner position in a survey for Latham and VanDebrake, Survey #04-106-C.


MONUMENT AND ACCESSORIES FOUND: None

MONUMENT SET:

Set a 2-3/8" brass cap on 1" X 30" galvanized iron pipe at the location shown on Survey #04-106-C 6" below gravel road surface.

MONUMENT MARKING DETAIL:

T4N R29E S11 S12 S14 S13 2011 LS2627



NEW ACCESSORIES:

WITNESS: Matthew Kenny, LSIT

A 5/8" X 20" steel rebar with blue plastic cap marked "UCPWD...LS2627" bears N63°02'07"W, 38.91 feet. UECA pole #4N29E119002 with bearing object tag bears 1 foot northwesterly from pin.

A 5/8" X 20" steel rebar with blue plastic cap marked "UCPWD...LS2627" bears N37 $^{\circ}$ 53'14"E, 22.51 feet. UECA pole #4N29E11901 with bearing object tag bears 1 foot northeasterly from pin.

A 5/8" X 20" steel rebar with blue plastic cap marked "UCPWD...LS2627" bears S18°50'27"E, 21.21 feet. UECA pole #4N29E149901 with bearing object tag bears 1 foot southeasterly from pin.

A 5/8" X 20" steel rebar with blue plastic cap marked "UCPWD...LS2627" bears S63°31'26"W, 41.98 feet. The middle post of a 3-post fence corner with bearing object tag bears 1 foot southwesterly from pin.

LOCATION AND COMMENTS:
Corner is 1/2 mile east of the
intersection of East Highland Extension
and North Loop Road at the intersection
of Kosmos Road and Darby Lane.
COMPASS DECLINATION:
N/A
FIRM/AGENCY:
Umatilla County Road Department
3920 Westgate
Pendleton, Oregon 97801
PARTY CHIEF:
Gary Roberts
NOTES:

SURVEYOR'S SEAL

REGISTERED
PROFESSIONAL
LAND SURVEYOR

LONG TO Hobert

OREGON
GARY P. ROBERTS
2627

RENEWS 12/31/2012