

RECORD OF LAND CORNER MONUMENTATION

NORTHWEST CORNER SECTION 32, T. 4 S., R. 33 E., W.M.

ORIGINALLY ESTABLISHED BY: George S. Pershin, U.S. Deputy Surveyor

CONTRACT NUMBER: 410

CONTRACT DATE: July 28, 1881

SUBSEQUENT SURVEYS: Recovered by W.L. Walker (Forest Service Employee), as evidenced by U.S. Forest Service corner card dated August 16, 1967

30	29			29	28
31	32			32	33
31	32			32	33
6	5			5	4

ORIGINAL DESCRIPTION: Set a basalt stone 17X12X6 ins. 12 ins. in ground for cor to Sec. 29, 30, 31 and 32 marked with one Notch on S. and 5 notches on E. edges from which  
A tamarack 8 ins. dia. brs. N.8°E. 30 lks. dist. marked T.4S. R.33E. S.29. BT  
A tamarack 8 ins. dia. brs. S.54°E. 12 lks. dist. marked T.4S. R.33E. S.32. BT  
A tamarack 8 ins. dia. brs. S.34°W. 18 lks. dist. marked T.4S. R.33E. S.31 BT  
A Pine 10 ins. dia. brs. N.48°W. 26 lks. dist. marked T.4S. R.33E. S.30 BT

1967 FOREST SERVICE DESCRIPTION: Stone 6" x 12" x 18"; 5 notches on one corner, possibly 1 notch on other corner. BTs. 20" Pine brs. N. 45°W. 16 Ft.; 14" Tam. brs. S. 75° E. 8 Ft.; 16" Tam. brs. N. 5° E. 18 Ft.

EVIDENCE FOUND: Found stone 17"x12"x6" laying flat with 2 other stones, with 5 notches on one edge and 1 notch on adjacent edge. From which, I also found the following original accessory evidence:

- ▶ A western larch, dead and down, 14" diameter, bears N.8°E., 20 ft.+/-, with partial blaze and scribing S29 BT
- ▶ A deteriorated western larch stump, 10"+/- diameter, bears S.54°E., 7 ft.+/-
- ▶ A western larch, 13" dbh, bears S.34°W., 11.85 ft., with healed single blaze, alive and vigorous
- ▶ A ponderosa pine, 22" dbh, bears N.48°W., 18.33 ft., with partially healed single blaze, alive and vigorous

I accept the position of the found marked stone for the section corner.

DESCRIPTION OF MONUMENTS AND ACCESSORIES SET AND METHODS USED: At the position of the found marked stone, I set a standard USFS 2 1/2" x 30" aluminum pipe with attached 3 1/4" aluminum cap, 28" in the ground. Raised a 3 ft. diameter mound of stone around the monument to top of cap. Cap is marked as shown below.

From which, I SCRIBE NEW BEARING TREES:

- ▶ A Douglas-fir, 10" dbh, bears N.43°E., 32.7 ft. marked T4SR33ES29 in upper blaze and BT in lower blaze.
- ▶ A Douglas-fir, 6" dbh, bears S.35°E., 37.7 ft. marked X in upper blaze and BT in lower blaze.

Also from which, ORIGINAL (LIVE) BEARING TREES BY PERSHIN:

- ▶ A western larch, 13" dbh, bears S.34°W., 11.85 ft., with healed single blaze
- ▶ A ponderosa pine, 22" dbh, bears N.48°W., 18.33 ft., with partially-healed single blaze

Deposited the marked stone inverted, NE and alongside the pipe. Painted a 6 inch red band around each live bearing tree, and also painted the blazes red, and attached USFS 54-3 and 54-9 signs to BT's. Used a magnetic compass with 14° East declination to measure bearings to accessories. Used an EDM device to measure distances to bearing trees, measuring to a 6" Mag Spike driven in the side-center at the root crown of each tree, with an attached 1 1/2" aluminum washer stamped PLS 69454. Set an aluminum guard post South, 2.4 ft. from the corner, with USFS 54-9 sign attached.

RESTORATION BY, STAMP AND DATE:

Work performed June 22, 2025

Jason L. Hatfield, PLS  
Vincent L. Kelly, Survey Tech

USDA FOREST SERVICE  
NORTHEAST OREGON LAND ZONE  
1550 Dewey Avenue, Suite A  
Baker City, OR 97814  
(541) 523-1283

RECEIVED BY  
Umatilla County Surveyor  
Date: 8/8/25  
Rec'd By: CT  
No.: 25-064-R

CORNER MONUMENT  
MARKED:

