

RECORD OF LAND CORNER MONUMENTATION

SOUTHEAST CORNER SECTION 32, T. 4 S., R. 33 E., W.M.

ORIGINALLY ESTABLISHED BY: George S. Pershin, U.S. Deputy Surveyor

CONTRACT NUMBER: 410

CONTRACT DATE: July 28, 1881

30	29			29	28
31	32			32	33
31	32			32	33
6	5			5	4

ORIGINAL DESCRIPTION: Set a basalt stone 16X12X7 ins. 11 ins. in ground for cor. to Sec. 32, 33, 4 & 5 marked with 2 notches on W. and 4 notches on E edges, 80 ft descent  
A Fir 18 ins. dia. brs. N.20°E. 25 lks. dist. marked T.4S. R.33E. S.33 B.T.  
A Pine 11 ins. dia. brs. S.14°E. 30 lks. dist. marked T.5S. R.33E. S.4. B.T.  
A Pine 6 ins. dia. brs. S.20°W. 27 lks. dist. marked T.5S. R.33E. S.5. B.T.  
A Pine 10 ins. dia. brs. N.68°W. 38 lks. dist. marked T.4S. R.33E. S.32. BT

EVIDENCE FOUND: Found stone 12"x12"x7" set 4" in the ground with no other stones, marked with 4 notches on east edge and 2 notches on west edge. From which, I also found the following original accessory evidence:

- A fir stump, 32" dbh, 9 ft. tall (broken), bears N.25°E., 16.3 ft. (measured to the face of the blaze), with scribe marks T4SR33ES33 in open upper blaze and BT in open lower blaze

I also searched for, but found no remains of the other three original bearing trees. I accept the position of the found marked stone for the section corner.

DESCRIPTION OF MONUMENTS AND ACCESSORIES SET AND METHODS USED: At the position of the found marked stone, I set a standard USFS 2 1/2" x 30" aluminum pipe with attached 3 1/4" aluminum cap, 28" in the ground. Raised a 3 ft. diameter mound of stone around the monument to top of cap. Cap is marked as shown below.

From which, I SCRIBE NEW BEARING TREES:

- A lodgepole pine, 8" dbh, bears N.39°E., 24.16 ft. marked T4SR33ES33 in upper blaze and BT in lower blaze
- A lodgepole pine, 5" dbh, bears S.59°E., 17.89 ft. marked X in upper blaze and BT in lower blaze
- A Douglas-fir, 8.5" dbh, bears S.39°W., 11.21 ft. marked T5SR33ES5 in upper blaze and BT in lower blaze
- A western larch, 10" dbh, bears N.81°W., 35.45 ft. marked T4SR33ES32 in upper blaze and BT in lower blaze

CORNER MONUMENT  
MARKED:



Deposited the marked stone inverted, North and alongside the pipe. Placed a plastic-encased magnet at the base of the pipe. Painted a 6 inch red band around each live bearing tree, and also painted the blazes red, and attached USFS 54-3 and 54-9 signs to BT's. Used a magnetic compass with 14° East declination to measure bearings to accessories. Used a steel tape to measure distances to bearing trees, measuring to a 6" Mag Spike driven in the side-center at the root crown of the tree, with an attached 1 1/2" aluminum washer stamped PLS 69454. Set an aluminum guard post North and alongside the mound of stone, with USFS 54-9 sign attached.

RESTORATION BY, STAMP AND DATE:

Work performed June 21, 2025

Jason L. Hatfield, PLS  
Vincent L. Kelly, Survey Tech

USDA FOREST SERVICE  
NORTHEAST OREGON LAND ZONE  
1550 Dewey Avenue, Suite A  
Baker City, OR 97814  
(541) 523-1283

RECEIVED BY  
Umatilla County Surveyor  
Date: 8/8/25  
Rec'd By: CT  
No.: 25-066-R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

JASON L. HATFIELD  
OREGON  
NOVEMBER 30, 2007  
JASON L. HATFIELD  
#69454

EXPIRES: 6/30/2027