CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. B-25

DIAGRAM	
T5S N 1/16 R33E -	R33½E
S1	\$3

History of original corner establishment:

No corner was originally set.

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner

At surveyed point set 3" brass tablet in mortar in large rock outcropping stamped.

N 1/16 R33½E R33½E S3 1980

Bearing Trees:

A Ponderosa Pine 5" dia. bears S77^oW, 106.2 ft., scribed N 1/16 S1BT. OR PLS 1294 A Juniper 9" dia., bears N51^oW, 29.7 ft., scribed N 1/16 S1 BT.

Attached 54-3 and 54-4 signs to both BTs. Attached brass washer stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs red. Attached 54-2 and 54-4 signs to metal post 6 ft. South of corner. Attached 54-2 and 54-9 signs to metal post 12 ft. West of corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OPEGON
SEPTEMBER 23, 1977
HOWARD L. PERRY
1 2 9 4

I hereby certify the above corner monument was established as herein described on June 23, 1980.

Witnesses: R. Orton G. Orton D. Allen

....

Office of	County Surveyor	County of	Umatilla
State of	Oregon , I hereby con	tify that the within ins	trument was filed in this office
for secord or	I grunten	nlier, 1980.	JL#
	(COUNTY OFFICIAL)	by	(DEPUTY)

Form R6-7100-57 (9/71)

: GPO 796-333

R-187-B