
History of original corner establishment:

Corner was originally established by Geroge S. Pershin under Contract No. 430, dated March 23, 1882. The original notes state that at the corner a 4inch square by 3 foot long was set in a mound of stone. No bearing trees were established.



No record of subsequent remonumentation found in County Records .

No evidence of original monument. Corner re-established by survey.

Description of monument and accessories I established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 10 inches in the ground and surrounded with a mound of stones to the cap.

Set steel fence post on section line N of corner and attached signs 54-2 and 54-4.

Established 1 new BT: A 12½" bull pine bears 563°E 123.0 ft scribed ½ \$15BT

Established 1 refrence monument: Set 2" x 30" iron pipe with brass cap for reference monument (RM) set 20" in ground to rock and surrounded with stone, bears N89°W 30.07 ft. marked: RM

New BT has a lower blaze scribed BT with brass washer stamped PLS 1106

30.07

See map of survey. This corner set July 2, 1979		PROFESSIONAL	T5S R33E
		LAND SURVEYOR	
Witnesses:	Greg Flowers Brent Reynolds	Willian R. Wells	4
		OREGON JULY 22, 1977 WILLIAM R. WELLS	S16 S15 1979 PLS 1106

(DEPUTY)

1-1-

Form R6-7100-57 (9/71)

RECEIVED BY

Umatilla County Surveyor

Date <u>August 20, 19.19.</u>

Rec'd By <u>M. Bughes</u>

No. <u>G-1134-B corespo</u>nding olrawing