

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

Index File No. A-21

**History of original corner establishment:**

The original corner was established BY Frank W. Campbell in 1881 under GLO Contract No. 380. The record reads: 79.90 intersect 1st std. Parallel 7.20 East of corner to Secs. 34 and 35 set a pine post for C.C. from which:


- A Pine 10 in. in diam. brs. N. 26° W. 23 lks Dist.
- A Pine 30 ins. in diam. brs. S. 24° W. 139 lks. Dist.
- A Fir 30 ins. in diam. brs. S. 20° E. 69 lks. Dist.

This corner was remonumented in 1976 by OPLS 598. His record reads:  
I did not find the original corner post. I establish this corner at record bearing and distance from the 3 original bearing trees as follows: The remains of a 10" pine stump bears N. 26° W. 15.2 feet scribing visible. A 36" Pine snag bears S. 24° W. 91.7 ft. mkd. R. 30 E., S. 20C, BT. A. 32" Fir stump bears S. 20° E. 45.5 ft. mkd. T6S. CC BT. At the corner point: Set a 2 1/2"x30" galvanized iron pipe 20" in the ground with brass cap marked as shown. Raised mound of stone, 3 ft. base to top of pipe. From which I scribe  
**NEW BEARING TREES:**

- A 10" Fir bears S. 59° E. 45.5 ft. mkd. T6S R30E S1 CC BT.
- A 18" Fir bears S. 53° W. 56.5 ft. mkd. T6S R30E S2 CC BT.

**Description of corner evidence found:**

Found steel pipe extending 10" above the ground with a 2 1/2" brass cap stamped as shown. in the diagram to the right. The monument is in a stone mound. Bearing trees found were: The remains of a Ponderosa Pine stump bear N26°W, 15.2' with visible scribing. A 36" Ponderosa Pine snag bears S24°W, 91.7' scribed R30E S2 CC BT. A 32" Fir stump bears S20°E, 45.5' scribed T6S CC BT. A 10" Douglas Fir bears S59°E, 45.5' with healed scribe. A 18" Douglas Fir bears S53°W, 56.5' with healed scribe.




T5S R30E	
S35	
S2	S1
T6S R30E	
CC	
1976	
OPLS 598	

**Description of monument and accessories I established to perpetuate the original location of this corner:**


Set a 30" aluminum pipe 22" in the ground at the intersection of the First Standard Parallel (projected through the found original corner of section 35 and the found original south 1/4 of section 35) and a line with bearing of N00°19'45"W projected through the found original northwest closing corner of section 1. This bearing was based on a previous survey by PLS 933 as given a survey recorded in Umatilla County in 1977 as M-64. Stamped the 2 1/2" aluminum cap as shown in the diagram to the right. Built a stone mound around the new monument. The new monument is about 3.45' south of the amended monument. Set a steel fence post 5' west of the monument and attached Forest Service Land Survey Monument and Property Boundary signs. Stamped the brass cap by OPLS598 "AM". Used old bearing trees as bearing trees for the new monument. These trees are located as follows with respect to the new monument. The 10" Douglas Fir bears S62°30'E, 44.2'. The 20" Douglas Fir bears S57°15'W, 51.0'. Repainted red bands and scribe blazes on all bearing trees. Attached Forest Service Land Survey Monument and Bearing Tree signs to all bearing trees.

T5S R30E	
S35	
S2	S1
T6S R30E	
CC	
1988	
PLS 852	

I certify the above corner points were perpetuated and established as hereon described on November 3, 1988.



*David L. Haddock*



Office of Survey Dept. County of Umatilla  
 State of OR, I hereby certify that the within instrument was filed in this office  
 for record on the 10<sup>th</sup> day of January, 1988  
David H. Humbria (COUNTY OFFICIAL) by Robert L. Ambs (DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY

Umatilla County Surveyor  
 Date 1-88  
 Rec'd by KA  
 No. 88-13-B

☆ GPO-798-276