CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM

υ..

T6S R30E + S11 4 S14

A 28"x18"x6" BASALT STONE IN A MOUND OF STONES

Description of corner evidence found:

28"x25"x6" BASAET STONE STUMP-HOLE N2OW 47.51

Description of monument and accessories I established to perpetuate the original location of this corner:

SET A 2"x30" IRON PIPE WITH A BRASS-CAP IN A MOUND OF STONES

THE MARKINGS ON THE BRASS-CAP ARE: T6S R30E

1 SII
4 SI4
1978
PLS 346

14" FIR \$33E 34.5' MARKED: 4 SI4 BT 12" PINE N34W 37.7' MARKED: 4 SII BT

ALL BT'S HAVE A RED-PAINTED STRIPE, BEARING TREE TAGS, AN ATTENTION TAG, AND A BRASS WASHER STAMPED PLS 346 NAILED TO THE LOWER BLAZE. THERE IS A STEEL FENCE POST NEAR THE CORNER.

REGISTERED OREGON LAND SURVEYOR

MAY 6, 1985
WAYNE O. HARRIS
346

Office of	f UMA.T.I.L.L.A hin instrument was filed	in this office	
toppeopon the day of by			1978
(COUNTY OFFICIAL)	(DEPUTY)		5-19
Form R6-7100-57 (9/71)			☆ CDO 700 500