## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

30" PINE SIOW 14LKS 8' x 8' x 13" BASALT STONE T6S H30E 4 812 14 813

Description of corner evidence found:

30" PINE DOWN SNAG, SCRIBING VISIBLE

Description of monument and accessories I established to perpetuate the original location of this corner:

SET A 30" x 3" IRON PIPE WITH BRASS-CAP MARKED

14" PINE S30W 26.5' MARKED 4 S13 BT 16" PINE NO4E 27.9' MARKED 4 S12 BT T6S R305 1 S12 4 S13 1978 PLS 346

ALL BT'S HAVE A RED PAINTED STRIPE, BEARING TREE SIGNS, AND ATTENTION SIGNS. THE NEW BT'S HAVE A BRASS WASHER STAMPED PLS-346 NAILED TO LOWER BLAZE. THERE IS A 6' STEEL FENCE POST WITHIN 5' OF THE CORNER.

REGISTERED
OREGON
LAND SURVEYOR

MAY 6, 1955
WAYNE O. HARRIS
346

Office of COUNTY SURVEYOR County of UMATILLA	
State of QR.E.G.O.N I hereby certify that the within instrument was filed in this office	
for record on the 13 day of October 1978	~ ~
for record on the 13. day of October 1978	5-2
(COUNTY OFFICIAL) (DEPUTY)	

Form R6-7100-57 (9/71)

☆ GPO 799-509