


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N - 7

History of original corner establishment:

This corner was originally established by Rufus S. Moore on July 4, 1881 under his contract number 382, as follows:

Set a basalt stone 18" x 12" x 10" in a mound of stone for the 1/4 section corner.



Description of corner evidence found:

Found a basalt stone, 18".x 12" x 10", marked "4" on the north face, in a mound of stones.

Description of monument and accessories established to perpetuate the original location of this corner:

Moving the corner stone aside, I set in it's place a 2 1/2" x 30" aluminum pipe with a 3 1/4" aluminum cap attached, 6" into the ground to bedrock. The cap is marked as shown in the diagram above. I built a mound of stones, 36" base x 18" high, around the pipe and placed the corner stone along the west side of the pipe. From which:

- A 19" Ponderosa Pine bears N8°W, 94.6 feet scribed "1/4 S17 BT".
- A 11" Ponderosa Pine bears N57°30'E, 71.0 feet scribed "1/4 S17 BT".
- A 12" Juniper bears S12°30'E, 78.5 feet scribed "1/4 S20 BT".
- A 17" Ponderosa Pine bears S79°W, 61.8 feet scribed "1/4 S20 BT".

All bearing trees have a 3/4" brass washer, marked "PLS 1636", nailed flush to the lower of double blazes and have signs 54-3, Bearing Tree, and 54-9, Land Survey Monument, attached.

I hereby certify the above corner position was perpetuated as hereon described on June 8, 1994.

Magnetic declination: 20° E.

NAD1983 Geographic Position (+ or - 2 to 5 meters)
Latitude 45-02-23.38 N
Longitude 119-00-45.16 W

Witness: Rachelle Fletcher

REGISTERED PROFESSIONAL LAND SURVEYOR

Dennis L. Gaylord

OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636

RENEWS 6/30/95

Office of COUNTY SURVEYOR County of UMATILLA
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

RECEIVED BY

Umatilla County Surveyor
Date 6-94
Rec'd By [Signature]
No. 94-692

D-7

★ GPO—798-276