Subdivisions of T. 1 N., R. 34 E.

	ains 0.00	Marked a pine, 36 ins. diam., $\frac{1}{4}$ S on W. side, for $\frac{1}{4}$ sec.
		cor., from which
		A pine, 12 ins. diam., bears North 60° E., 29 lks.
		dist.
		No other tree in limits.
		Raised mound of stone alongside.
4	7.50	Canyon, course W.
. 5	0.00	Top of ridge.
8	0.00	Set stone, 12x10x8 ins., 9 ins. in ground, for cor. to
		secs. 23, 24, 25 and 26, marked two notches on S. and
		one notch on East edges, from which
		A pine, 40 ins. diam., bears South 40°East, marked
		S 25 T l N R 34 E B T; also
		A pine, 30 ins. diam., bears N.25°E., marked Sec. 24
		В Т.
		No other trees in limits.
		Raised mound of stone alongside.
		Land, rolling.
		Some pine timber in flats.
		NA CONTRACTOR AND ADMINISTRATION OF THE PROPERTY OF THE PROPER
		Soil, 2nd rate.
	İ	East on random between secs. 24 and 25.
		Var. 20° E.
4	0.00	Set temporary \(\frac{1}{4} \) sec. cor.
8	0.35	Intersect T. line, 14 lks. S. of cor. to secs. 19, 24,
		25 and 30. Thence I run
		S. 89°54'W. on true line.
3	5.25	Spring branch, 1 lk. wide, course W.
4	0.17	Set a basalt stone, 18x16x12 ins., 14 ins. in the ground,
		marked $\frac{1}{4}$ S on N. side, for $\frac{1}{4}$ sec. cor., from which
		A fir, 5 ins. diam., bears S.5°W., 42 lks. dist.,
		marked 1 S B T.
		A pine, 30 ins. diam., bears N.80°W., 109 lks. dist.,
		marked & S B T.
		Raised mound of stone over it.
	z 17.	O MAN D C C C C C C C C C C C C C C C C C C
5	3.75	A gulch bears S., water in small pools.

KILHAM 156