Subdivisional Lines, T. 1 N., R. 35 E.

	Chains	Subdivisional Lines, T. 1 N., R. 35 E.	ř.
	, onario	North bet. Secs. 4 & 5.	
	n	Descend steep mountain side.	
7	35.00	Bottom canon.	-80
	40.00		
		cor., from which	
		A Pine 8 ins. in diam. bears S85°E. 25 lks. dist.,	
	2011	marked 18. B. T.	
		A Fir 14 ins. in diam. bears N.80°W. 15 lks. dist.,	
		marked 4 S.B.T.	
r.	42.00	Summit small sharp ridge E.	†400
	47.00	Gulch N.E. and begin ascent.	-50
	80.38	Intersect Tp. line 365 lks. E. of cor. to secs. 32 & 33,	
		T 1 N R 35 E. Set basalt stone 14 x 10 x 5 ins., 10 ins. in the ground for Closing cor. to secs. 4 & 5, marked with	
)		4 notches on E. and 2 notches on W. edges and C.C. on S. face; pits impracticable; raised mound of stone over it. Land, mountainous 42 chs.	
	·	Soil, 4th rate. Timber, Pine, fir and tama rack.	
		From cor. to Secs. 31 & 32 on S. bdy. of Tp. I run	
		North bet. secs. 31 and 32.	
~		Var. 21° East. Through heavy timber.	
	40.00	Tamarack 4 ins. diam. marked \(\frac{1}{4} \) S on W face for \(\frac{1}{4} \) S. cor.,	
		from which	
		A Red fir 10 ins. in diam. bears N.80°W.31 lks. dist.,	
		marked & S.B.T.	*
)		A Pine 20 ins. in diam. bears S.15°E.36 lks. dist.,	
	1.6	marked & S.B.T.	
	43.50	Spring branch 3 lks. N.W.	
	80.00	Set stone 9 x 8 x 7 ins., 6 ins. in the ground for corner	
	14.00	to secs. 29, 30, 31 and 32, marked with 1 notch on Saand	
i.i.	470.7	5 notches on E. edges, from which	
10		A Pine 10 ins. in diam. bears N.75° E. 72 lks. dist., marked T 1 N R 35 E S29 B. T.	

_C

KILHAN 1967