Resurvey of the Base Line through Range 36 East.

Set a post 3 ft. long, 3 ins. square, 24 ins. in the
ground, for \(\frac{1}{4}\) sec. cor. marked B L \(\frac{1}{4}\) S on N. face,
from which,
A pine, 12 ins. diam., bears N.30°W., 123 lks. dist.
marked 4 S B T.
No other tree within limits and raised a mound of
stone around post.
The old $\frac{1}{4}$ sec. cor., a post in mound of rock bears W.
7.65 chs. dist. I destroy both post and mound.
Top of ridge about 100 ft. above gulch, course S.
Bottom of gulch about 100 ft. below ridge, course S.
Top of ridge about 100 ft. above gulch, course S.
Descend about 100 ft. to
Set a post 4 ft. long, 4 ins. square, 24 ins. in the
ground, for cor. to secs. 32 and 33 marked B L T 1 N
R 36 E S 33 on E., and S 32 on W. faces with 4 notches
on E. and 2 notches on W. faces, from which,
A fir, 8 ins. diam., bears N.45°E., 24 lks. dist.,
marked T 1 N R 36 E S 33 B T.
A tamarack, 14 ins. diam., bears N.55 W., 33 lks.
dist., marked T-1 N R 36 E S 32 B T.
No other tree within limits, and
raised a mound of stone around post.
OBSTRUCTURE CONTRACTOR AND ADDRESS AND ADD
The old sec. cor., a post bears W. 8.75 chs. dist.
I destroy same and obliterate the marks on old bearing trees, 2 pines.
TOTAL CONTROL OF THE PROPERTY
Land, mountainous.
Soil, 2nd rate.
Timber, scattering fir, pine and tamarack.
West on Poss Titus on S. hours
West on Base Line on S. boundary of sec. 32.
Var. 21°E.

Descend.

40.00 Set a post 3 ft. long, 3 ins. square, 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor. marked B L  $\frac{1}{4}$  S on N. face, from which,