Subdivisions of T. 1 N., R. 36 E. Surveyed by Herman D. Gradon, contract No. 452. Dated June 16, 1882.

Chains	Preliminary to subdividing this township I ran North on a
	Blank on the E. boundary of sec. 36, and at 40.03 chs.
	I found the \(\frac{1}{4}\) sec. cor., and at 80.04 chs. I found the
	sec. cor. I have resurveyed the Base Line which is the
	S. boundary and do not again retrace it. My compass
	will, therefore, run the same line as the exterior
	boundaries and the chaining practically agrees.
	Survey commenced September 13, 1882, with a Burt's
	improved Solar compass.
	I commence at the cor. to secs. 35 and 36 on the Base Line,
14.0	which is a post 4 ins. square marked B L T 1 N R 36 E
4)	S 36 on E. and S 35 on W. faces with 1 notch on E. and
200	5 notches on W. faces with a mound of stone around post.
	Thence I run
· .	North between secs. 35 and 36.
	Var. 214 °E.
3,00	The state of the s
10.00	Bottom of gulch about 150 ft. below ridge, course W.
20.00	Top of ridge about 150 ft. above gulch, course W.
40.00	Set a basalt stone, 12x12x5 ins., 8 ins. in the ground,
	for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, and raised a
	mound of stone alongside.
45.00	Enter heavy timber, course N.W.
80.00	A point about 500 ft. below last ridge. Set a post, 4 ft.
	long, 4 ins. square, 24 ins. in the ground, for cor. to
	secs. 25, 26, 35 and 36 marked T 1 N S 25 on N.E., R 36
	E S 36 on S.E., S 35 on S.W., and S 26 on N.W. faces
	with 1 notch on S. and E. edges, from which
*	A fir, 15 ins. diam., bears N.70°E., 28 lks. dist.,
	marked T 1 N R 36 E S 25 B T.
	Secretary Control of the Control of
	A fir, 12 ins. diam., bears S.80°E., 95 lks. dist.,
	marked T 1 N R 36 E S 36 B T.
	A fir, 24 ins. diam., bears S.20 W., 13 lks. dist.,
	marked T 1 N R 36 E S 35 B T.
	A fir, 7 ins. diam., bears N.25°W., 50 lks. dist.,
	marked T 1 N R 36 E S 26 B T.