Subdivisions of T. 1 N., R. 36 E.

	Chains 40.00	Set a basalt stone, 12x8x6 ins., 8 ins. in the ground,
		for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, and raised a
(a)		mound of stone alongside.
- 72	51.50	.Top of ridge about 75 ft. above gulch, course W.
١.	70.50	Bottom of gulch about 100 ft. below ridge, course W.
	75.00	Top of ridge about 75 ft. above gulch, course W.
		Descend about 50 ft. to
æ	80.00	Set a post 4 ft. long, 4 ins. square, 24 ins. in the
11.2		ground, for cor. to secs. 9, 10, 15 and 16, marked with
1.5		4 notches on S. and 3 notches on E. edges, from which
		A fir, 12 ins. diam., bears N.18°E., 17 lks. dist.,
		marked T 1 N R 36 E S 10 B T.
g []		A fir, 15 ins. diam., bears S.65°E., 28 lks. dist.,
		marked T 1 N R 36 E S 15 B T.
	*	A fir, 24 ins. diam., bears S.50 W., 52 lks. dist.,
		marked T 1 N R 36 E S 16 B T.
		A fir, 14 ins. diam., bears N.50°W., 52 lks. dist.,
		marked T 1 N R 36 E S 9 B T.
		Land, mountainous.
		Soil, sandy loam, 2nd rate.
	-	Timber, scattering fir and pine with dense undergrowth
		of buck brush.
		East on a random line between secs. 10 and 15.
		Var. 22 3/4°E.
-	00'	Ascend.
	40.00	Set temporary 4 sec. cor.
	80.56	A point on mountain side about 1000 ft. above last sec.
	v ,	cor. Intersect 15 lks. N. of the cor. to secs. 10, 11,
		14 and 15.
		Thence I run
		N.89°54'W. on a true line between secs. 10 and 15.
5	40.28	Set a basalt stone, 12x12x10 ins., 8 ins. in the ground,
- 1	1 .	for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, and raised a
		mound of stone alongside.
- 1	54.070.00 TREAT	The cor. to secs. 9, 10, 15 and 16.