## Subdivisions of T. 1 N., R. 37 E.

-	Chains	
	- a	A fir, 30 ins. diam., bears N.56°E., 130 lks. dist.,
		marked T 1 N R 38 E S 30 B T.
		A fir, 30 ins. diam., bears S.82°E., 104 lks. dist.,
		marked T 1 N R 38 E S 31 B T.
	10.08	With mound of stone alongside.
		Thence I run
		N.89°45'W. on a true line between secs. 25 and 36.
	39.94	Set a basalt stone, 13x9x8 ins., 9 ins. in the ground,
		for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which,
		A fir, 4 ins. diam., bears N.60 W., 52 lks. dist.,
		marked 1 S B T.
		A fir, 10 ins. diam., bears S.10°W., 21 lks. dist.,
-		marked 1 S B T.
	79.88	The cor. to secs. 25, 26, 35 and 36.
		Land, mountainous.
		Soil, sandy loam, 2nd rate.
		Heavily timbered with fir and tamarack.
	3 4 8	North between secs. 25 and 26.
		Var. 184°E.
	1.00	Ascend.
	40.00	Ascend. Set a basalt stone, 14x10x8 ins., 9 ins. in the ground,
	40.00	
	40.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground,
	40.00	Set a basalt stone, $14x10x8$ ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which,
	40.00	Set a basalt stone, $14x10x8$ ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which, A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,
	40.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.
	40.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,
		Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,  marked \( \frac{1}{4} \) S B T.
	64.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,  marked \( \frac{1}{4} \) S B T.  Top of ridge, about 400 ft. above sec. cor., course W.
	64.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,  marked \( \frac{1}{4} \) S B T.  Top of ridge, about 400 ft. above sec. cor., course W.  Set a post, 4 ft. long, 4 ins. square, 24 ins. in the
	64.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,  marked \( \frac{1}{4} \) S B T.  Top of ridge, about 400 ft. above sec. cor., course W.  Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 23, 24, 25 and 26, marked
	64.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,  marked \( \frac{1}{4} \) S B T.  Top of ridge, about 400 ft. above sec. cor., course W.  Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 23, 24, 25 and 26, marked  T 1 N S 24 on N.E., R 37 E S 25 on S.E., S 26 on S.W.
	64.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked \( \frac{1}{4} \) S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,  marked \( \frac{1}{4} \) S B T.  Top of ridge, about 400 ft. above sec. cor., course W.  Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 23, 24, 25 and 26, marked  T 1 N S 24 on N.E., R 37 E S 25 on S.E., S 26 on S.W.  and S 23 on N.W. faces, with 2 notches on S. and 1
The second secon	64.00	Set a basalt stone, 14x10x8 ins., 9 ins. in the ground, for ½ sec. cor. marked ½ on W. face, from which,  A fir, 16 ins. diam., bears N.55°E., 46 lks. dist.,  marked ½ S B T.  A fir, 36 ins. diam., bears N.40°W., 13 lks. dist.,  marked ½ S B T.  Top of ridge, about 400 ft. above sec. cor., course W.  Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 23, 24, 25 and 26, marked  T 1 N S 24 on N.E., R 37 E S 25 on S.E., S 26 on S.W.  and S 23 on N.W. faces, with 2 notches on S. and 1 notch on E. edges, from which,

KILHAM 1983