## Subdivisions of T. 1 N., R. 37 E.

Chains	manual for I are seen manifest I C as W for Di-
	ground, for \( \frac{1}{4} \) sec. cor. marked \( \frac{1}{4} \) S on W. face. Dug
	pits, $18x18x12$ ins., N. and S. of cor., $5\frac{1}{2}$ ft. dist.,
Sk 7.5	and raised a mound of earth $1\frac{1}{2}$ ft. high, $3\frac{1}{2}$ ft. base
	alongside.
63.00	Bottom of gulch, about 150 ft. below ridge, course W.
80.00	Set a basalt stone, 12x12x8 ins., 8 ins. in the ground,
8 I (9)	for cor. to secs. 26, 27, 34 and 35, marked with 1
	notch on S. and 2 notches on E. edges, from which,
	A fir, 5 ins. diam., bears N.15°E., 45 lks. dist.,
	marked T 1 N R 37 E S 26 B T.
8	A fir, 5 ins. diam., bears S.60°E., 72 lks. dist.,
	marked T 1 N R 37 E S 35 B T.
	No other tree within limits.
	and raised a mound of stone alongside.
	Land, mountainous.
	Soil, sandy loam and stony, 2nd and 3rd rate.
	Timber, scattering fir and pine with dense undergrowth
	of fir, pine and mountain laurel.
(4)	East on a random line between secs. 26 and 35.
	Var. 21°E.
1150	Ascend.
40.00	Set temporary 1/4 sec. cor.
42.00	Top of ridge, about 800 ft. above cor., course S.W.
70.00	Bottom of gulch, about 400 ft. below ridge, course S.W.
79.80	Intersect 15 lks. S. of the cor. to secs. 25, 26, 35 and
333333	36.
1/2	Thence I run
	S.89°54'W. on a true line between secs. 26 and 35.
39.90	Set a basalt stone, 16x10x4 ins., 11 ins. in the ground,
	for \(\frac{1}{4}\) sec. cor., marked \(\frac{1}{4}\) on N. face, and raised a
	mound of stone alongside.
79.80	The cor. to secs. 26, 27, 34 and 35.
2000	
20	Land, mountainous.
	Soil, 2nd rate.  Timber, scattering fir and pine with dense undergrowth of
	mountain laurel.