Subdivisions of T. 1 N., R. 37 E.

C	hains	Land, mountainous.
		Soil, stony, 3rd rate.
	2	Timber, scattering fir and tamarack.
		Dense undergrowth of fir, tamarack, buck brush and alder.
		The same of the sa
	40 00	East on a random line between secs. 16 and 21.
		Var. 20½°E.
		Ascend steep hill.
	40.00	Set temporary 1 sec. cor.
	80.32	A point about 1500 ft. above sec. cor. Intersect 50 lks.
	00.05	S. of the cor. to secs. 15, 16, 21 and 22.
		Thence I run
		Amount of the control
	40.16	S.89°39'W. on a true line between secs. 16 and 21.
	40.10	Set a basalt stone, 14x14x4 ins., 9 ins. in the ground,
-5	Cent	for \(\frac{1}{4}\) sec. cor. marked \(\frac{1}{4}\) on N. face, from which,
		A pine, 28 ins. diam., bears N.60°W., 166 lks. dist.,
		marked 1/4 S B T.
1		A fir, 12 ins. diam., bears S.75 W., 111 lks. dist.,
		marked ½ S B T.
1	80.32	The cor. to secs. 16, 17, 20 and 21.
0	**	Land, mountainous.
		Soil, 2nd rate.
		Timber, scattering fir and pine.
ĺ		
-		North between secs. 16 and 17.
	40	Var. 202°E.
	0.50	A creek, 12 lks. wide, runs S.W.
2	23.00	Top of ridge, about 150 ft. above creek, course S.E.
3	36.00	Bottom of gulch, about 100 ft. below ridge. A brook, 5
		lks. wide, runs S.E.
4	40.00	Set a basalt stone, 24x16x4 ins., 18 ins. in the ground,
		for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which,
		A pine, 6 ins. diam., bears S.70°E., 19 lks. dist.,
		marked 4 S B T.
		A fir, 6 ins. diam., bears N.70 W., 32 lks. dist.,
		marked 1/4 S B T.

KILWAM 156741