Resurvey of South Bdy. of T. 2 N., R. 37 E.

Chains	of the S.W. bearing tree, which has been destroyed.
	I set an ironstone, 20x20x12 ins., 15 ins. in the
	ground, at the same point, for cor. of secs. 4, 5, 32
	and 33, marked with 4 notches on E. and 2 notches on
	W. edges, from which,
	A fir, 12 ins. diam., bears S.40°W., 2.09 chs. dist.,
50	marked T 1 N R 37 E S 5.B T.
	The other trees bear as stated by the surveyor
	general.
	Land, mountainous.
	Soil, loam and stony, 2nd and 3rd rate.
3	Timber, fir, pine, spruce and tamarack.
	Undergrowth, mountain laurel, huckleberry and small firs.
9	Mountainous land. 80.36 chs.
	The state of the s
:	S.88°48'W. on old township line between secs. 5 and 32.
	Descend gradually through scattering timber.
26.00	Enter dense undergrowth, bears N. and S.
30.24	Spring branch, 5 lks. wide, course N.10 W.
00,01	Ascend over rolling land through heavy timber.
39.90	Intersect old \(\frac{1}{4}\) sec. cor., which is a post, badly decayed,
,00.00	marked obliterated and witnessed as described by the
	surveyor general. I set a basalt stone, 15x8x6 ins.,
	10 ins. in the ground, at the same point, for $\frac{1}{4}$ sec.
	cor., marked \(\frac{1}{4}\) on N. face.
	N.89°57'W.
50.30	Spring branch, 3 lks. wide, in ravine, 50 ft. deep,
50.00	course N.20°E.
74.75	sweetstatus and a state of the
79.00	Through scattering timber, bears N. and S.
	Enter raging forest fire, bears N. and S.
80.19	Intersect old cor. of secs. 5, 6, 31 and 32, which is a
	post almost burned away and bearing trees as described
	by the surveyor general are all missing. I reestablish
	the old cor. at the same point as follows: Set a
	basalt stone, 20x12x4 ins., 15 ins. in the ground, for
300	cor. of secs. 5, 6, 31 and 32, marked with 5 notches on