## Subdivisional Lines, T. 1 S., R. 34 E., W.M.

8 4	Chains	A tamarack, 16 ins. diam., brs. S.50° W., 55 lks. di	Feet
- 31		marked & S.,B.T.	.50.
	44.50	Gulch, course W.	700
	56.50	m.,	-300
			1200
1 5	68.50	Canyon, course W.	-200
	78.75	Top of hill, course W.	\$200
13	80.00	Set basalt stone, 16 x 10 x 8 ins., 11 ins. in ground,	
		marked 3 notches on S. and 1 notch on E. edges. for	
		Cor. to Secs. 13, 14, 23 & 24. Raised mound of stone a	<b>.</b> –
		round it. Pits impracticable.	
	-	Land; mountainous and broken, 80.00 chs.	
160		No timber. Good bunch grass.	
(3)		Soil; 3rd rate.	1
10			
		E. on random bet. Secs. 13 & 24.	
		Var. 16° 45' E.	
8	40.00	Set temp. 1 Sec. Cor.	1
	800600	Intersected Tp. line, 25 lks. S. of Cor. to Secs. 13, 18,	
77		19 & 24.	
		Thence I run,	
		S.89° 49' W. on a true line.	
	6.00	Leave timber.	
	40.30	Set basalt stone, 12 x 10 x 7 ins., 8 ins. in ground,	
		marked & on N. face, for & Sec. Cor. Raised mound of	
4		. stone around it. Pits impracticable.	
. 1	59.00	Canyon, course S.W.	-600
	78.00	Top of ridge, course S.W.	+400
)	80.60	To Cor. to Secs. 13, 14, 23 & 24.	
)	CONTRACTOR CONTRACTOR	Land; rough and mountainous, 80.60 chs.	
		Good bunch grass.	
		Soil; 4th rate.	
		2011, 2011 1400.	
		N. bet. Secs. 13 & 14.	
	1		
	17 00	Var. 16° 45' E.	
. 1	13.00	Rimrock, 20 ft. high.	\$200