Resurvey Portion N. Bdy., T.2 S., R.34 E., W.M.

Chains	the line bet. Secs. 1 & 36, at 42.28 chs., fall 495 lks	= et
	N. of the 4 Sec. Cor. and at 80.27 chs., fall 112 lks.	
· ·	N. of the Cor. of Secs. 1, 2, 35 & 36.	()
	W., retracing line bet. Secs. 2 & 35; at 40.20 chs., fall	
	29 1ks. N. of 1 Sec. Cor. and at 79.94 chs., fall 91 1ks	a de la companya de l
	N. of Cor. of Secs. 2, 3, 34 & 35.	
	W., retracing line bet. Secs. 3 & 34; at 40.00 chs., find	
	no trace of the 4 Sec. Cor., and at 77.77 chs., fall 167	
	lks. N. of Cor. to Secs. 3, 4,33 &34.	
	S. 89° 25' W., retracing the S. Bdy. of Secs. 33, T.1 S.,	
	R.34 E., and at 3.91 chs., fall 4 lks. S. of Closing	6
	Cor. of Secs. 3 & 4, T. 2 S., R. 34 E.	
	***	
15.0	The Closing Cor. of Secs. 3 & 4 is a basalt stone, 15 x 8 x	
	10 ins., above ground, firmly set, marked X on top,	
111	3802 880 CAT St 6811 16 WELL 10 \$100 ARR 117	
	with 6 notches on S. face, witnessed as described by	ل
100	the Surveyor General.	
	At a point, 4 lks. S. of the old Closing Cor.	
	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in are	
	ground, for Closing Cor. of Secs. 3 & 4, with brass	
	cap, marked,	
	T2S R34E	31667
	1917	
2	and raise mound of stone, 2 ft. base, 12 ft. high, S.	
	of Cor.	
	Thence	
	N.89° 25' E., resurveying the N. Bdy. of Sec. 3.	11
0	Ascend 66 ft. over mountainous land to	
3.91	Intersect old Cor. of Secs. 33 & 34, which is a basalt	
	stone, frimly set, marked as described by the Surveyor	
	General.	
8 19	At a point, 1 lk. N. of true Cor.	
100	Set basalt stone, 15 x 10 x 8 ins., 10 ins. in ground, for	
	witness Cor. to the Cor. of Secs. 33 & 34, marked with	
-	The state of the s	

3 notches on E. & W. edges. 33 on N.W., 34 on N.E. and