Subdivisional Lines, T.1 S., R.35 E., W.M.

	Chains	127	00
	Charns	Sec. Cor., marked & S. on N. face, from which,	ee
).	A pine, 24 ins. diam., brs. N.50°E.,78 lks. dist.,	
30 13		marked & S.,B.T.	
	100	A tamarack, 16 ins. diam., brs. S.45°E.,67 lks. dist.,	
		marked & S.,B.T.	
: *	47.00	Intersect Tp. line,4.70 chs. N. of Cor. to Secs.12 & 13	
		of T.1 S.,R.34 E. S	
	1	Set basalt stone, 12 x 10 x 8 ins., 8 ins. in ground, for	
	t	Closing Cor. to Secs. 7 & 18, marked	
		C.C. on E. face	
		4 notches on S. and	
	10	2 notches on N. edges.	
		Raised stone mound around it. Pits impracticable.	
		Land; rolling.	
		Soil; 2nd rate.	
16		Pine and fir timber with openings. Good bunch and pine	
		grass.	
		S. bet. Secs. 17 & 18.	
		Var. 22° 15' E.	
		Enter pine opening.	
	40.00	Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground for 1	
		Sec. Cor., marked & S. on W. face, from which,	
	2	A pine, 24 ins. diem., brs. S.65°E.,38 lks. dist.,	
6		marked & S.,B.T.	
1.		A pine, 16 ins. diam., brs.S.85°W.,32 lks. dist.,	
		marked & S.,B.T.	
	55.00	Enter thick timber.	
	80.00	Set post, 4 ft. long, 4 ins. sq.,2 ft. in ground, for Cor.	
		to Secs. 17, 18, 19 & 20, marked	
		S.19 on S.W.	
		S.18 on N.W.	
•		T.1 S.,S.17 on N.E.	
	16	R.35 E.,S.20 on S.E. and	
		5 notches on E. and	
	7(6)	3 notches on S. edges.	_