

Subdivisional Lines, T.1 S., R.36 E., W.M.

Chains	Feet
	S.32 on N.W. faces, with 4 notches on E. and 2 notches on W. edges, from which, A tamarack, 12 ins. diam., brs. N.30°W., 16 lks. dist., marked T.1 S., R.36 E., S.32, B.T. A tamarack, 18 ins. diam., brs. S.34°W., 30 lks. dist., marked T.2 S., R.36 E., S.5, B.T. A pine, 18 ins. diam., brs. S.69°E., 13 lks. dist., marked T.2 S., R.36 E., S.4, B.T. A tamarack, 24 ins. diam., brs. N.82°E., 35 lks. dist., marked T.1 S., R.36 E., S.33, B.T.
I run	
	N. bet. Secs. 32 & 33.
	Var. 20°E.
	Through timber
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S. on W. face, from which, A tamarack, 9 ins. diam., brs. S.50°E., 9 lks. dist., marked $\frac{1}{4}$ S., B.T. A tamarack, 7 ins. diam., brs. N.50°W., 13 lks. dist., marked $\frac{1}{4}$ S., B.T.
62.50	A wagon road, course E. & W.
80.00	Set basalt stone, 13 x 10 x 8 ins., 9 ins. in ground for Cor. to Secs. 28, 29, 32 & 33, marked with 1 notch on S. and 4 notches on E. edges, from which, A pine, 8 ins. diam., brs. N.35°E., 57 lks. dist., marked T.1 S., R.36 E., S.28, B.T. A pine, 5 ins. diam., brs. S.40°E., 43 lks. dist., marked T.1 S., R.36 E., S.33, B.T. A pine, 7 ins. diam., brs. S.30°W., 26 lks. dist., marked T.1 S., R.36 E., S.32, B.T. A tamarack, 24 ins. diam., brs. N.60°W., 20 lks. dist marked T.1 S., R.36 E., S.29, B.T.
	Land; mountainous.
	Soil; sandy loam, 2nd rate.
	Heavily timbered with fir, tamarack and pine.