		Subdivisions, T. 2 N., R. 36 E.
	Chains	Intersect E. boundary 10 lks. N. of the cor. to secs. 13,
	80.63	24, 18 & 19, which is a basalt stone 18 x 9 x 6 ins.,
		Agency Motor at Technology Control of Contro
		marked with 3 notches on N & S edges, from which
¥ .		A fir, 8 ins. in diam. bears N. 60° E. 21 lks.,
		dist., marked T 2 N.R 37 E. S 18 B.T.
		A pine, 16 ins. in diam. bears S. 10° W. 40 lks.,
		dist., marked T 2 N.R 36 E. S24 B.T.
		A fir, 12 ins. in diam. bears N. 30° W. 21 lks.
. 1		dist., marked T 2 N.R 36 E.S 13 B.T.,
		and a mound of stone alongside.
		Thence, I run
	0.0	N. 89° 56' W. on a true line bet. secs. 13 & 24.
	40.31	Set a basalt stone 18 x 10 x 5 ins., 12 ins. in the
		ground for 1 sec. cor., marked 1 on N. face, from which,
9		A fir, 6 ins. in diam. bears N. 5° W. 49 lks. dist.
	-	marked \(\frac{1}{4}\) S. B. T.
tis	2	
		A fir, 9 ins. in diam. bears S. 40° W. 40 lks.dist.
	12	marked & S. B. T.
	80.63	The cor. to secs. 13, 14, 23 & 24.
	8	Land, mountainous.
-		Soil, sandy loam and stony, 2nd & 3rd rate.
		Heavily timbered with fir and tamarack. Dense under-
		growth of young fir, tamarack and spruce.
		192 7/
		From the cor, to secs. 2, 3, 34 & 35, on the S. boundary,
		which is a basalt stone 15 x 12 x 10 ins., marked with
1		2 notches on E. and 4 notches on W. edges, with mound
		of stone alongside,
		I run
	11 (44)	North bet. secs. 34 & 35.
		Var. 21° East.
	2015/02/02	Descend about 100 ft. to
	7.00	Bottom of gulch, course S.W.
	40.00	Set a basalt stone 14 x 10 x 6 ins., 9 ins. in the
		ground for \(\frac{1}{4} \) sec. cor., marked \(\frac{1}{4} \) on W. face and raised