OF

		Subdivisions, T. 2, N., R. 36 E.
	Chains	
	10.00	A perpendicular basaltic bluff, 20 ft. high.
9.0	40.05	Set an iron stone 15 x 12 x 6 ins., 10 ins. in the ground
	- 2	for \(\frac{1}{4} \) sec. cor., marked \(\frac{1}{4} \) on N. face, marked \(\frac{1}{4} \) on N.
		face, from which
(b) (1)		A fir, 12 ins. in diam. bears S. 10° E., 15 lks.
		dist., marked 1 S.12, B.T.
11 8		Afir, 10 ins. in diam. bears N. 21° E., 28 lks.
		dist., marked \(\frac{1}{4} \) S. 1, B. T.
	41.75	E.edge of plateau or summit of divide.
		Over nearly level ground.
	45.00	Summit of divide, 400 ft. above sec. cor., course N.30°
	2	E., S.
	LIFE E	Descend gradually.
92	66.25	Pack trail, bears N. 20° E., S. 20° W.
	67.25	W. edge of plateau, bears N. 30° E., S. 70° W.
	01.20	Descend through dense thicket of small firs.
	76.00	Leave thicket, bears N.10° E., S.10° W.
	80.10	The cor. of secs. 1, 2, 11 and 12.
	80.10	
		Land, level and mountainous.
		Soil, stony; lst ½, rich loam; 2nd ½, 4th and lst rate.
		Timber, fir, pine, tamarack, cherry and maple.
3 5		Undergrowth, laurel and small firs.
		Mountainous land, 61.00 chs.
		N. 0° 01' W. on random line bet. secs. 1 and 2.
	40.00	Set temp. 4 sec. cor.
	71.81	Intersect the N. bdy. of Tp, 24.24 chs. E. of the cor. of
	100	secs. 1, 2, 35 and 36, which is a basalt stone, 6 x 7x6
		ins. above the ground, marked and witnessed as described
		by the Surveyor General. Set iron stone, 20x12x8 ins.,
	e e ga	15 ins. in the ground for closing cor. for secs. 1 and
		2, marked C. C. on S. face, and with 1 notch on E. and
		5 notches on W. faces, from which
	V=3	A fir, 6 ins. in diam. bears S. 24° W., 150 lks. dist.
		marked T.2 N., R.36 E., T. 2, B.T.
F.		

KILHAM 158741