

Subdivisions, T. 2 N., R. 36 E.

Chains	
	Thence, I run S. $0^{\circ} 02'$ E. on random line bet. secs. 14 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
81.10	Intersect the E. and W. line, 2.06 chs. E. of the cor. of secs. 14, 15, 22 and 23, which is a basalt stone $6 \times 14 \times 8$ ins. above ground, marked, witnessed as de- scribed by the Surveyor General. Set basalt stone, $15 \times 10 \times 8$ ins., 10 ins. in the ground for closing cor. for secs. 14 and 15, marked C.C. on N. face and 2 grooves on E. and 3 grooves on S. edges, from which, A fir, 12 ins. in diam. bears N. 35° E., 14 lks. dist., marked T. 2, N., R. 36 E., S. 14, B.T. A fir, 18 ins. in diam. bears N. 31° W., 59 lks. dist., marked T. 2, N., R. 36 E., S. 15, B.T. I destroy all marks on old cor., pertaining to the survey N.
	From the closing cor., I run, N. $0^{\circ} 02'$ W. on true line, bet. secs. 14 and 15. Descend N. slope of hill, through heavy timber.
23.72	Ravine, 50 ft. deep, course N. 30° E. Leave heavy timber, bears N. 30° E., S. 30° W. Hill bears N. 60° W., S. 60° E.
40.75	Enter scattering timber, bears N. and S.
41.10	Set basalt stone $15 \times 10 \times 8$ ins., 10 ins. in ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, from which A fir, 12 ins. in diam., bears N. 32° E., 39 lks. dist., marked $\frac{1}{4}$ S. 14, B.T. A fir, 10 ins. in diam. bears N. 2° W., 20 lks. dist. marked $\frac{1}{4}$ S. 15, B.T. This cor. stands about 800 ft. below the closing cor.
43.00	Very steep descent.
46.10	Foot of hill, 850 ft. below closing cor. Dry bed of stream, 10 lks. wide, course N. 80° W. Water comes to surface about 5.00 chs. below line.