## Chains

Since the point for the cor. common to secs. 25 and 36 falls on the old sec. cor., I reestablish the old sec. cor. as a cor. common to secs. 25, 30, 31 and 36 as follows:

Destroy old post and set an ironstone, 15x10x5 ins., 10 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, marked with 5 notches on N. and 1 notch on S. edges, from which,

- A fir, 12 ins. diam., bears N.77°E., 22 lks. dist., marked T 2 N R 38 E S 30 B T.
- A fir, 24 ins. diam., bears S.59°E., 86 lks. dist., marked T 2 N R 38 E S 31 B T.
- A fir, 30 ins. diam., bears S.12 W., 110 lks. dist., marked T 2 N R 37 E S 36 B T.
- A fir, 26 ins. diam., bears N.40 W., 13 lks. dist., marked T 2 N R 37 E S 25 B T.

Land, mountainous.

Soil, loam and stony, 2nd and 3rd rate.

Timber, fir, pine, spruce, larch and tamarack.

Undergrowth, mountain laurel, huckleberry, small firs, yew and vine maple.

Mountainous or heavily timbered land. 79.70 chs.

N.0°18'W. on old township line between secs. 25 and 30. Ascend along E. slope through heavy timber and scattering undergrowth.

- 18.00 Creek, 3 lks. wide, in ravine, 150 ft. deep, course S.80 W.
- 28.75 Top of ridge, 200 ft. above creek, bears E. and W. Descend.
- Intersect old \(\frac{1}{4}\) sec. cor., which is a post badly decayed marked and witnessed as described by the surveyor general. I destroy old post and set new post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for\(\frac{1}{4}\)sec. cor., marked \(\frac{1}{4}\) S 30 on E. face. I destroy all marks, which pertain to the survey E.