Subdivisions	of	175	9	N.	R.	37	E.	W.	M.
Subdivisions	OI	25.	~	110	11.	01	+40		111 .

Chai	Subdivisions of T. 2 N. R. 37 E. W. M.
0	Ascend through very scattering timber.
61.0	1 Set ironstone, 28x24x10 ins., in mound of stone, for 1
	Sec. cor. marked 1 on N. face. No trees in limits.
	Raise mound of stone, 2 ft. base, 12 ft. high N. of cor.
100	Pits impracticable. This cor. stands about 400 ft. below
	top of ridge.
64.0	O Enter heavy pine timber, bears N. and S.
71.0	Top of ridge point, 100 ft. above 1 Sec. cor., bears
	N. and S.
	Descend through scattering timber along S. slope.
1	of mountain.
93.2	5 Enter heavy timber, bears N. and S.
99.2	O Foot of mountain, 400 ft. below ridge point.
	Over bottom land not subject to immidation.
99.5	O S. Fork of Umatilla River, 25 lks. wide, slow current,
	stony bottom, course N. 10° E.
101.0	1 The cor. of Secs. 5, 6, 7 and 8.
2 2	Land, mountainous.
	Soil, loam and stony; 1st 3rd and 4th rate.
	Timber, pine, fir, tamarack and cottonwood.
	Mountainous, land, 101.01 chs.
1 1	N. 0° 05' W. on random line bet. Sess. 5 and 6.
40.00	Set temp. 1 Sec. cor.
75.25	Intersect N. bdyof Tp. 6.51 chs. E. of the 4 Sec. cor.,
	which is a baselt stone, 4x10x8 ins. above ground,
v	marked 4 on N. face, from which.
*.	A fir, 14 ins. diam., bears N. 61° E., 81 lks.
	Dist., marked 1 S. 32 B.T.
	At point of intersection. set basalt stone, 20x15x4 ins.15
10	ing in the ground, for closing cor. of Secs. 5 and 6,
33	marked C C on S. face; with 1 groove on W. and 5
	grooves on E. faces, from which
	A fir, 14 ins. diam., bears S. 72° B., 98 lks.
	dist., marked T 2 N R 37 E., S 5 B T.
	A fir, 12 ins. diam., bears S. 85° W., 197 lks.

KILEAN 150741

5 83