

North Bdy., T. 3 S., R. 33 $\frac{1}{2}$ E., W.M.

Chains	Feet
	<p>W. on random line on S. Bdy. of Secs. 36, 35 & 34. Var. 19°30' E.</p> <p>I set temp. Cors. at every 40 & 80 chs. and at 2 miles, 6 chs. & 70 lks., intersect the W. Bdy. of the Tp., 70 lks. S. of Cor. to Tps. 2 & 3 S., R.33$\frac{1}{2}$ E.</p> <p>The correction for the true line will therefore be 34 lks. N. to the mile and its bearing will be S.89° 46' E.</p>
	<p>From the Cor. to Tps. 2 & 3 S., R.33$\frac{1}{2}$ E., I run S.89° 46' E. on true line bet. Secs. 3 & 34. Var. 20° E.</p>
6.70	<p>Set a post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for Cor. to Secs. 2, 3, 34 & 35, marked T.2 S., S.35 on N.E. R.33$\frac{1}{2}$ E., S.2 on S.E. T. 3 S., S.3 on S.W. and S.34 on N.W. faces, with 2 notches on E. and 1 notch on W. edges, from which, A pine, 10 ins. diam., brs. N.35° E., 33 lks. dist., marked T.2 S., R.33$\frac{1}{2}$ E., S.35,B.T. A pine, 36 ins. diam., brs. S.73° E., 12 lks. dist., marked T.3 S., R.33$\frac{1}{2}$ E., S.2,B.T. A tamarack, 24 ins. diam., brs. S.40° W., 6 lks. dist., marked T.3 S., R.33$\frac{1}{2}$ E., S.3,B.T. A fir, 8 ins. diam., brs. N.31° W., 22 lks. dist., marked T.2 S., R.33$\frac{1}{2}$ E., S.34,B.T. Land; hilly. Soil; 2nd rate. Heavily timbered with pine, fir and tamarack.</p>
	<p>S.89° 46' E. on true line bet. Secs. 2 & 35. Var. 20° E.</p>
40.00	<p>Set basalt stone, 13 x 12 x 6 ins., 9 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which, A tamarack, 10 ins. diam., brs. N.50° E., 60 lks. dist., marked $\frac{1}{4}$ S.,B.T.</p>