Exterior & Subdivisional Lines, T.2 S., R.33 E., W.M.

	Chains 80.00	Intersect S. Bdy. of Tp. at Cor. for Secs.1, 2, 35 & 36,
	£3	which is a basalt stone, 12 x 10 x 8 ins., 2 ins. in
		ground, marked 1 notch on E. and 5 notches on W., from
		which,
		A pine, 20 ins. diam., brs. N.54°E., 49 lks. dist.,
	9 10	marked T.2 S.,R.33½E.,S.36,B.T.
		A pine, 10 ins. diam., brs. S.29°E., 75 lks. dist.,
		marked T.3 S., R.33 E., S.1, B.T.
		A pine, 6 ins. diem., brs. S.50°W.,36 lks. dist.,
		marked T.3 S., R.332E., S.2, B.T.
		A tamarack, 22 ins. diam., brs. N.48° W., 37 lks. dist.
		marked T.2 S., R. 33 E., S. 35, B.T.
		Thence I run
		N. on true line bet. Secs. 35 & 36.
		Var.20°00'E.
		Through thick timber on mountain.
	26.00	Descend mountain.
	40.00	Set basalt stone, 14 x 10 x 5 ins., 10 ins. in ground, for
		1 Sec. Cor., marked 1 on W. face. Raised mound of earth
		and stone, 2 ft. high x 32 ft. base over Cor., on N.
		hillside, from which,
	8	A fir, 6 ins. diam., brs. S.50° W., 25 lks. dist.,
		marked \( \frac{1}{4} \) S., B.T.
		and the state of t
		A pine, 8 ins. diem., brs. N.52° E.,26 lks. dist.,
	. ".	markedd 4.S., B.T.
	51.50	Canyon, course N.W. Ascend steep mountain ridge, through
	. 1	dense brush and timber.
	52.50	Summit of ridge falls S.85°W. Descend.
	64.00	Birch Creek, 20 lks. wide, runs N.65° E. Ascend.
	75.00	Summit. Descend.
	80.00	The Cor. to Secs. 25, 26, 35 & 36.
		Land; mountainous, 80 chs.
		Timber; pine, fir & tamarack, with dense undergrowth of
		same, throughput the whole line.
9	•= <sup>1</sup>	Soil; 4th rate. Some grass.
		CONTRACTOR SUPPLIES DESCRIPTION WORKSTONE