

Exterior & Subdivisional Lines, T. 2 S., R. 33 E., W.M.

Chains		Feet
	over stone on W. hillside, about 2 chs. W. of rock ledge. Pits impracticable.	
80.54	The Cor. to Secs. 28, 29, 32 & 33. Land; mountainous, 80.54 chs. Soil; stone 4hh.rate. Timber; pine, fir & tamarack, 20.00 chs. dense. No undergrowth. Good grass. Sept. 20, 1891.	
	S. bet. Secs. 32 & 33. Var. 20° 00' E.	
2.50	Leave timber.	
14.50	Enter thick brush.	
23.50	Leave " " , timber, scattering.	
38.50	Summit of ridge falls W. Descend 10°.	
40.00	Set basalt stone, 18 x 8 x 4 ins., 12 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, and raised mound of stone, 2 ft. high x $3\frac{1}{2}$ ft. base over Cor., on S. hillside, from which, A pine, 36 ins. diam., brs. S. 45° W., 123 lks. dist., marked $\frac{1}{4}$ S., B.T. No other tree in limits. Pits impracticable.	
41.00	Ravine, course W. Ascend 10°	- 75
53.40	Intersect S. Bdy. of Tp., 765 lks. E. of Cor. to Secs. 2, 3, 34 & 35, which is a basalt stone, 14 x 8 x 6 ins., 8 ins. in ground, in mound of stone, 1 ft. high x 2 ft. base, marked 4 notches on E. and 2 notches on W., from which, A fir, 8 ins. diam., brs. N. 13° E., 62 lks. dist., marked T. 2 S., R. 33 E., S. 35, B.T. A pine, 14 ins. diam., brs. S. 50° W., 110 lks. dist., marked T. 3 S., R. 33 E., S. 3, B.T. A fir, 8 ins. diam., brs. N. 20° W., 59 lks. dist., marked T. 2 S., R. 33 E., S. 34, B.T. I destroy all marks referring to this Tp., and, at point of intersection, set Set basalt stone, 18 x 10 x 3 ins., 12 ins. in ground, for Closing Cor. to Secs. 32 & 33, marked 4 notches on E. face	