Subdivisional Lines, T.2 S., R.33 E., W. M. As surveyed by James P. Currin & James E. Noland, U.S.Dep. Surveyors Under their Special Contract,
Dated May 4th, 1887.

Chains		
3	From the Cor. to Secs. 1, 2, 35 & 36 on N. Bdy. of Tp.,	
40	I run	108
	S. on true line bet. Secs. 1 & 2	
	Var.22 °E.	
30.00	Draw, N.W.	
40.00	Set basalt stone, 10 x 10 x 16 ins., 10 ins. in ground,	
	for \$ Sec. Cor., marked \$ on W. face,	
	From which,	
	A pine, 36 ins. diam., brs. S.72°E., 3.65 lks. dist.,	
	marked \(\frac{1}{4}\) S., B.T.	
	No other tree in limits.	
	Raised mound of stone over Cor., 18 ins. high, with 32 ft.	
	base.	
80.00		
	Set basalt stone, 7 x 8 x 12 ins., 8 ins. in ground, for	
	Cor. to Secs. 1, 2, 11 & 12, marked with 5 notches on	
2 4	S. and one on E. edges, over which, I raised mound of)
	stone, 2 ft. high with 4 ft. base.	
	Land; gently sloping, toward the North.	
	Line mostly on top of ridge.	
1.0	Scattering pine & fir timber.	
	Good bunch grass.	
19 11	Soil; 1st rate.	
	E .	1
	E. onrandom line bet. Secs. 1 & 12.	
	Var.21°45'E.	
40.00	Set temp. 1 Sec. Cor.	_
80.30	Intersect line at Cor. to Secs. 1 & 12 on E. Bdy.	
4 81	Ver.25°50'E.	~
	Thence W. on true line.	
10.15	Canyon, North.	
20.00	Summit of ridge, N.	
40.15	Set stone, 8 x 8 x 8 ins., 12 ins. in ground, for 1 Sec.	
	Cor., marked 1 S. on N. face,	
1 315-22-00	From which,	
1		Ü.,